

Kanaflex®

KANALINE FW

Exposed helix . . . acts as a scuff guard, permits wash water to flow underneath and allows easy drag.

Braided reinforcement . . . permits use under higher working pressure. Will take full vacuum.

Smooth bore . . . provides unrestricted flow.

Clear sidewall . . . permits visual check of material flow.

FDA compliant . . . manufactured from compounds that meet FDA and 3-A nontoxic specifications.

SPECIFICATIONS

SIZE	OUTSIDE DIAMETER Inches	PITCH Inches	MIN. BENDING RADIUS 72°F, Inches	WORKING PRESSURE 72°F, P.S.I.	BURSTING PRESSURE 72°F, P.S.I.	VACUUM RATING 72°F, In. / Hg.	WEIGHT Lbs. / Ft.
1½"	2.01	0.39	3.0	110	360	28.0	0.56
2"	2.58	0.41	4.5	100	300	28.0	0.75
3"	3.60	0.59	8.0	100	280	28.0	1.20
4"	4.72	0.65	10.0	75	230	28.0	1.74

Kanaflex®
CORPORATION

800 Woodlands Parkway
Vernon Hills, IL 60061

DISTRIBUTED BY:

GOODYEAR
RUBBER PRODUCTS INC.

Call Toll Free: **1-866-711-4673**
WebSales@GoodyearRubberProducts.com

**We Ship
World Wide**