

Kanaflex® ST 200 SFG

Grounding wire . . . prevents static buildup that can reduce material flow and cause arcing.

Clear sidewall . . . permits visual check of material flow.

Smooth bore . . . provides unrestricted material flow.

Corrugated O.D. . . . provides lightweight flexibility.

FDA Compliance . . . manufactured from compounds that meet FDA and 3-A nontoxic specifications.

SPECIFICATIONS

SIZE	OUTSIDE DIAMETER Inches	PITCH Inches	MIN. BENDING RADIUS 72°F, Inches	WORKING PRESSURE 72°F, P.S.I.	BURSTING PRESSURE 72°F, P.S.I.	VACUUM RATING 72°F, In. / Hg.	WEIGHT Lbs. / Ft.
1½"	1.88	0.35	2.0	45	149	29.8	0.44
2"	2.36	0.39	2.6	40	132	29.8	0.58
2½"	2.87	0.56	2.6	35	115	29.8	0.75
3"	3.50	0.59	2.8	35	115	29.8	1.07
4"	4.59	0.65	4.3	30	100	29.8	1.52

Kanaflex®
CORPORATION

800 Woodlands Parkway
Vernon Hills, IL 60061

DISTRIBUTED BY:

GOODYEAR
RUBBER PRODUCTS INC.

Call Toll Free: **1-866-711-4673**
WebSales@GoodyearRubberProducts.com

**We Ship
World Wide**