

INDUSTRIAL / HEAVY DUTY INDUSTRIAL BELT

#26C 2 Ply 220 1/8 x Bare Back Moderate Oil Resistance

Excellent light to medium duty conveyor belt has moderately thick cover with moderate oil resistance to wood chips and many non-petroleum oils. Often used in handling wood products and recycling, where materials contain food oils and greasy waste materials.

Temperature range: 0° F to 250° F. **Thickness:** 1/4". **Weight:** .150 piw.

Minimum pulley diameter: 10". **Recommended fasteners:** #140 Solid Plate, #187 Staple, #375 Bolt On, #R2 Rivet.

Part Number: 20029690



#8 2 Ply 220 1/8 x 1/16 Grade 2

Excellent medium duty conveyor belt with medium thick abrasion resistant covers. Good selection for sand and gravel portable screening applications on trough conveyors. SBR covers provide excellent flex life and resistance to abrasion, making it a good buy for most conveyor applications.

Temperature range: -25° F to 225° F. **Thickness:** 5/16". **Weight:** .167 piw.

Minimum pulley diameter: 10". **Recommended fasteners:** #140 Solid Plate, #550 Bolt On, #R5 Rivet.

Part Number: 20013600



#9 2 Ply 220 3/16 x 1/16 Grade 2

Excellent heavy duty conveyor belt with thicker abrasion resistant covers. Excellent general purpose sand and gravel belt. Often used in scrap metal plants and foundries where high impact is not a problem, also used in the wood products industry. Excellent base belt for road machinery. SBR cover provides excellent flex life and resistance to abrasion, making it a good buy for heavy duty conveyor applications.

Temperature range: -25° F to 225° F. **Thickness:** 11/32". **Weight:** .195 piw.

Minimum pulley diameter: 12". **Recommended fasteners:** #190 Solid Plate, #550 Bolt On, #R5 Rivet.

Part Number: 20017500



#10A 3 Ply 225 1/16 x Bare Back Grade 2

Versatile medium duty belt for handling lumber, pea gravel, and other bulk materials. Flexible belt able to negotiate small pulleys.

Temperature range: -25° F to 225° F. **Thickness:** 7/32". **Weight:** .122 piw.

Minimum pulley diameter: 8". **Recommended fasteners:** #2 Hook, #187 Staple, #25 Alligator, #R2 Rivet.

Part Number: 20029655



HEAVY DUTY INDUSTRIAL BELT

#11 3 Ply 330 3/16 x 1/16 Grade 2

Excellent heavy duty conveyor belt with moderately thick abrasion resistant covers. Often used in the aggregate industry for rock conveying and heavy loads. Good selection for other heavier duty applications on troughing conveyors, such as for scrap metal, foundries, and high tensions. SBR covers provide excellent flex life and resistance to abrasion, making it a good buy for most conveyors.

Temperature range: -25° F to 225° F. **Thickness:** 13/32". **Weight:** .205 piw.

Minimum pulley diameter: 16". **Recommended fasteners:** #190 Solid Plate, #550 Bolt On, #R5 1/2 Rivet.

Part Number: 20023005



#12 3 Ply 330 1/4 x 1/16 Grade 2

Excellent heavy duty conveyor belt with extra thick abrasion resistant covers. Often used in aggregate applications where severe cover wear is normally experienced. Good selection for other heavy duty applications on troughing conveyors. SBR covers provide excellent flex life and resistance to abrasion, making it a good buy for most conveyor applications.

Temperature range: -25° F to 225° F. **Thickness:** 15/32". **Weight:** .215 piw.

Minimum pulley diameter: 16". **Recommended fasteners:** #190 Solid Plate, #550 Bolt On, #R5 1/2 Rivet.

Part Number: 20026039

