

PVC / RMV BELT



#67A PVC 200 Black Cover x Friction Surface

Heavier duty PVC belt proven for long wearing, high performance, and problem free material handling. Regularly used in the feed and grain industries. Also popular as heavy duty package and bulk product conveyor belt for both slider and roller bed conveyors.

Temperature range: 20° F to 180° F. **Thickness:** 15/64". **Weight:** .117 piw. **Minimum pulley diameter:** 6". **Recommended fasteners:** #4 Hook, #187 Staple, #27 Alligator.

Part Number: 20038207



#69A PVC 200 Black Oil Resistant Static Conductive Cover x Cover

Heavier duty PVC belt proven for long wearing, high performance and problem free material handling applications. Regularly used in the feed and grain industries. Also popular as heavy duty package and bulk product conveying belt for both troughed roller bed conveyors and elevator applications.

Temperature range: 20° F to 180° F. **Thickness:** 1/4". **Weight:** .142 piw. **Minimum pulley diameter:** 6". **Recommended fasteners:** #4 Hook, #187 Staple, #27 Alligator, #R5 Rivet.

Part Number: 20038206



#69B PVC 250 Black Oil Resistant Static Conductive Cover x Cover

Commonly used for elevator belting in the feed and grain industries. Because of the low temperature, oil resistance, and static conductive qualities of this specification, it provides excellent service life in most agricultural environments. This belt won't mildew or rot, is moisture resistant, and has high bolt retention for bucket attachments.

Temperature range: 20° F to 180° F. **Thickness:** 5/16". **Weight:** .150 piw. **Minimum pulley diameter:** 8". **Recommended fasteners:** #140 Solid Plate, #550 Bolt On, #R5 Rivet, #35 Alligator.

Part Number: 20038500

PVC ELEVATOR BELT



#66A PVC 150 Black Oil Resistant Cover x Cover

Proven belt for long wearing, high performance, problem free material handling applications. Ideal for moving bulk materials, chemicals, fertilizers, and moderate sized product loads. Ideal for a variety of roller bed and troughed applications. Characteristics include low stretch, high strength, good fastener retention, with superior rip, tear, and gouge resistance.

Temperature range: 20° F to 180° F. **Thickness:** 13/64". **Weight:** .100 piw. **Minimum pulley diameter:** 4". **Recommended fasteners:** #3 Hook, #187 Staple, #25 Alligator.

Part Number: 20038199



#70A PVC 200 White Oil Resistant Cover x Cover

Excellent two cover white belt for heavy duty use on conveyors with FDA requirements, such as flour milling, sugar, or bulk foods. Characteristics include low stretch, high bolt retention, and an SOR compound that is not affected by grains. Meets FDA; is USDA accepted.

Temperature range: 20° F to 180° F. **Thickness:** 1/4". **Weight:** .142 piw. **Minimum pulley diameter:** 6" for conveyor / 8" for elevator.

Recommended fasteners: #4 Hook, #187 Staple, #27 Alligator, #R5 Rivet.

Part Number: 20038208



#69A PVC 200 Black Oil Resistant Static Conductive Cover x Cover

Heavier duty PVC belt proven for long wearing, high performance and problem free material handling applications. Regularly used in the feed and grain industries. Also popular as heavy duty package and bulk product conveying belt for both troughed roller bed conveyors and elevator applications.

Temperature range: 20° F to 180° F. **Thickness:** 1/4". **Weight:** .142 piw. **Minimum pulley diameter:** 6". **Recommended fasteners:** #4 Hook, #187 Staple, #27 Alligator, #R5 Rivet.

Part Number: 20038206

22 BELT SAMPLES ARE AVAILABLE •