

Working Tension PIW	Temp Range	Minimum Pulley Dia	Weight PIW	Maximum Roll Width	FDA USDA	Flexco #	Clipper #	DESCRIPTION ABBREVIATION KEY
160#	-25°F to 225°F	4"	.095	60"		125, 7	1	BB = Bare Back Brush = Brushed Bottom C = Conveyor CBS = Cover Both Sides CD = Cold CR = Cross Rigid CT II = Chevron Top II E = Elevator FR = Fire Retardant FS = Friction Surface GR 2 = Grade 2 (SBR) H = Hot IMPG = Impregnated MOR = Moderate Oil Resistance MRT = Mini Roughtop MSHA = Mine Safety Health Act MSK = Mini Skim Coat OR = Oil Resistant ORS-HMB = Oil Resistant Hot Asphalt Poly = Polyester PU = Polyurethane PVC = Poly Vinyl Chloride RMV = Rubber Modified Vinyl RT = Roughtop SC = Static Conductive Tex = Texture
120#	20°F to 180°F	2 1/2"	.100	72"		125, 15	1	
100#	20°F to 180°F	2"	.085	72"		125, 7	1SP	
120#	20°F to 180°F	2"	.085	72"		62, 7	1SP	
200#	20°F to 180°F	4"	.130	72"		187, 27		
120#	20°F to 180°F	2 1/2"	.090	72"		125, 7	1	
150#	20°F to 180°F	3"	.110	72"		125, 20	2	
150#	20°F to 180°F	3"	.110	72"		125, 20	2	
105#	0°F to 250°F	2 1/2"	.060	72"		125, 7	1	
135#	0°F to 250°F	3 1/2"	.085	72"		125, 15	2SP	
56#	20°F to 180°F	1 1/2"	.047	78"	*	62, 1	25LP	
220#	-25°F to 225°F	12"	.210	72"		190, 375, R5		
220#	0°F to 250°F	12"	.210	72"		190, 375, R5		
330#	-25°F to 225°F	18"	.260	72"		190, 550, R5 1/2		
330#	0°F to 250°F	18"	.250	72"		190, 550, R5 1/2		
220#	0°F to 250°F	10"	.185	72"		190, 375, R5		
330#	0°F to 250°F	16"	.225	72"		190, 550, R5		
60#	20°F to 180°F	2"	.047	72"		1	25LP	
100#	20°F to 180°F	1 1/2"	.070	72"		62, 7	1SP	
150#	20°F to 180°F	3"	.080	72"		62, 7	1SP	
120#	20°F to 180°F	2 1/2"	.100	72"		125, 15	1	
100#	20°F to 180°F	2"	.085	72"		125, 7	1SP	
120#	20°F to 180°F	2"	.085	72"		62, 7	1SP	
120#	20°F to 180°F	2 1/2"	.088	72"		125, 7	1	
120#	20°F to 180°F	2 1/2"	.090	72"		125, 7	1	
150#	20°F to 180°F	3"	.110	72"		125, 20	2	
150#	20°F to 180°F	3"	.110	72"		125, 20	2	
120#	20°F to 180°F	2 1/2"	.100	72"		125, 15	1	
100#	20°F to 180°F	2"	.065	72"		62, 7	25LP	
120#	20°F to 180°F	2"	.050	72"		125, 15	1	
120#	20°F to 180°F	2"	.075	72"		125, 15	1	
120#	20°F to 180°F	2"	.075	72"		125, 15	1	
100#	20°F to 180°F	2"	.070	72"		62, 7	1SP	
120#	20°F to 180°F	2 1/2"	.090	72"		125, 20	2	
150#	20°F to 180°F	4"	.100	72"		187, 25	3	
150#	20°F to 180°F	3"	.100	72"		125, 20	2	
200#	20°F to 180°F	6"	.117	72"		187, 27	4	
200#	20°F to 180°F	6"	.142	72"		187, 27, R5	4	
220#	20°F to 180°F	8"	.126	72"		187, 27, 140, 375, R5	4	
250#	20°F to 180°F	8"	.150	72"		140, 550, R5, 35		
150#	20°F to 180°F	4"	.100	72"		187, 25	3	
200#	20°F to 180°F	6c, 8e	.142	72"		187, 27, R5	4	
200#	20°F to 180°F	6"	.142	72"		187, 27, R5	4	
250#	20°F to 180°F	8"	.150	72"		140, 550, R5, 35		
350#	20°F to 180°F	8c, 12e	.158	72"		140, 550, R5, 45		
450#	20°F to 180°F	10c, 14e	.175	72"		190, 550, R5, 45		