

# Hose Fittings



## Male Hose Nipples

BAND-IT's distinctive design assures the user of a tight fitting connection with excellent sealing characteristics, maximum flow, low profile and superior performance when used with BAND-IT clamping systems. These screw machined nipples have National Pipe Threads.

## Stainless Steel Male Hose Nipples

For severely corrosive conditions, BAND-IT's machined hex nipple is available in Type 316 stainless steel.



## Female Swivel Hose Nipples

Distinctive hose stem design. Nut end has conical seat to seal with the BAND-IT Male Hose Nipple. The large diameter hole provides maximum flow.

### Male Hose Nipples

### Plated Carbon Steel - NPT

Package Quantity - 12

Number of Clamps Per Nipple - 1

Cat. No.	Hose ID		NPT Inches	Dia of Hole		Shank Length		Weight	
	Inches	mm		Inches	mm	Inches	mm	Lbs	Kg
◆E004	1/4	6.35	1/8	.188	4.78	.87	22.23	.4	.2
◆E006	1/4	6.35	1/4	.188	4.78	1.03	26.19	.8	.3
◆E008	3/8	9.53	1/8	.234	5.94	1.07	27.20	.6	.3
◆E010	3/8	9.53	1/4	.234	5.94	1.07	27.20	.7	.3
◆E012	3/8	9.53	3/8	.234	5.94	1.07	27.20	1.2	.5
◆E014	3/8	9.53	1/2	.234	5.94	1.07	27.20	2.0	.9
◆E018	1/2	12.70	1/4	.266	6.76	1.35	34.29	1.4	.6
◆E020	1/2	12.70	3/8	.359	9.12	1.35	34.29	1.3	.6
◆E022	1/2	12.70	1/2	.375	9.53	1.35	34.29	2.1	.9
◆E028	5/8	15.88	1/2	.500	12.70	1.36	34.54	2.0	.9
◆E030	5/8	15.88	3/4	.500	12.70	1.36	34.54	2.6	1.2
◆E032	3/4	19.05	1/2	.500	12.70	1.38	35.15	3.0	1.4
◆E034	3/4	19.05	3/4	.625	15.88	1.38	35.15	2.8	1.3
◆E036	3/4	19.05	1	.625	15.88	1.38	35.15	4.1	1.9
◆E038	1	25.40	3/4	.750	17.86	1.78	45.31	4.0	1.8
◆E040	1	25.40	1	.875	22.23	1.78	45.31	4.6	2.1
◆E042	1 1/4	31.75	1	.922	23.42	1.78	45.31	7.3	3.3
◆E044	1 1/4	31.75	1 1/4	1.109	28.17	1.78	45.31	8.2	3.7
◆E046*	1 1/2	38.10	1 1/2	1.344	34.14	1.90	48.49	11.5	5.2

\*Round Profile, not Hex

### Male Hose Nipples

### Type 316 Stainless Steel - NPT

Package Quantity - 1

Cat. No.	Hose ID		NPT Inches	Dia of Hole		Shank Length		Weight	
	Inches	mm		Inches	mm	Inches	mm	Lbs	Kg
◆E606	1/4	6.35	1/4	.188	4.78	1.03	26.19	.06	.03
◆E612	3/8	9.53	3/8	.234	5.94	1.07	27.20	.09	.04
◆E622	1/2	12.70	1/2	.375	9.53	1.35	34.29	.19	.09
◆E634	3/4	19.05	3/4	.625	15.88	1.38	35.15	.25	.11
◆E640	1	25.40	1	.875	22.23	1.78	45.31	.38	.17

### Female Swivel Hose Nipples

### Plated Carbon Steel - NPSC

Package Quantity - 12

Minimum Number of Clamps Per Stem-1

Cat. No.	Hose ID/ NPSC Inches	ID/ NPSC mm	Shank Length		Weight	
			Inches	mm	Lbs	Kg
◆E106	1/4	6.35	1.06	27.0	.7	.3
◆E112	3/8	9.53	1.31	33.4	1.2	.6
◆E122	1/2	12.70	1.37	34.9	1.7	.8
◆E134	3/4	19.05	1.37	34.9	3.0	1.3
E140	1	25.40	1.71	43.7	4.1	1.8