



## Tri-Lokt® Hose Nipples Type 316 Stainless Steel

The successful Tri-Lokt® Nipple with the same exclusive features designed for higher pressure hose applications in stainless steel with stainless steel tie strips for superior corrosion resistance.

## Tri-Lokt® Female Swivel Couplings

Nut end has conical seat to seal with a Tri-Lokt® Male Nipple of comparable size.

*Caution: Hose and nipples should never be operated in excess of the maximum working pressure established by the hose manufacturer.*

## Replacement Tri-Lokt® Yokes and Tie Strip Kits

### Replacement Tri-Lokt SS Yokes

Package Quantity - 12

Cat. No.	Size	
	Inches	mm
H022	1/2	12.70
H034	3/4	19.05
H040	1	25.40

### Replacement Tri-Lokt® SS Tie Strip Kits

Package Quantity -1 set Strips & Jr. Clamps

Cat. No.	Size	
	Inches	mm
H604	1 1/4	31.8
H614	1 1/2	38.1
H624	2	50.8
H634	2 1/2	63.5
H644	3	76.2
H654	4	101.6
H769	5	127.0
H774	6	152.4

### Tri-Lokt Hose Nipples Plated Carbon Steel - NPT - Swaged

Nipples Complete With Tie Strips

Cat. No.	Hose ID		NPT Inches	Shank Length		No. of Clamps Per Nipple	Pkg Qty	Weight	
	Inches	mm		Inches	mm			Lbs	Kg
◆H600	1 1/4	31.75	1 1/4	2.75	69.9	4	1	1.2	.6
◆H610	1 1/2	38.10	1 1/2	2.75	69.9	4	1	1.4	.7
◆H620	2	50.8	2	2.75	69.9	4	1	2.1	1.0
H630	2 1/2	63.5	2 1/2	4.50	114.3	6	1	3.8	1.7
◆H640	3	76.2	3	4.50	114.3	6	1	5.0	2.3
◆H650	4	101.6	4	4.50	114.5	6	1	6.8	3.1
◆H656	5	127.0	5	6.50	165.1	8	1	11.4	5.2
◆H658	6	152.4	6	8.00	203.2	10	1	16.9	7.7

See page 38 for clamp width information.

### Tri-Lokt Hose Nipples Type 316 Stainless Steel - NPT - Swaged

Nipples Complete With Tie Strips

Cat. No.	Hose ID		NPT Inches	Shank Length		No. of Clamps Per Nipple	Pkg Qty	Weight	
	Inches	mm		Inches	mm			Lbs	Kg
S600	1 1/4	31.8	1 1/4	2 3/4	69.8	4	1	1.3	.6
◆S610	1 1/2	38.1	1 1/2	2 3/4	69.8	4	1	1.4	.6
◆S620	2	50.8	2	2 3/4	69.8	4	1	2.1	.9
S630	2 1/2	63.5	2 1/2	4 5/8	117.5	6	1	3.5	1.6
◆S640	3	76.2	3	4 5/8	117.5	6	1	4.6	2.1
◆S650	4	101.6	4	4 5/8	117.5	6	1	6.8	3.1

See page 38 for clamp width information.

### Tri-Lokt Female Swivel Coupling Plated Carbon Steel - NPSC

Package Quantity -12

Number of Clamps Per Coupling - 2

Cat. No.	Hose ID/NPSC		Shank Length		Weight	
	Inches	mm	Inches	mm	Lbs	Kg
H222	1/2	12.70	1.19	30.2	3.2	1.4
H234	3/4	19.05	1.50	38.1	5.7	2.6
H240	1	25.40	1.50	38.1	8.6	3.9

See page 38 for clamp width information