

2" Quick Clean, High Capacity Y-Strainer

FEATURES

- Heavy duty fiberglass-reinforced polypropylene
- 316 stainless steel screens
- Screens 8" long full flow
- 3" cam lever cap for easy cleaning
- Viton O-ring
- EPDM gaskets standard

QUICK CLEAN HIGH CAPACITY POLY Y-STRAINERS

ITEM	DESCRIPTION	PART NO.	MESH
D	2" Y-Strainer	200A	6,14,40,80

NOTE: Please specify stainless steel mesh (6-14-40-80) 14 mesh is standard.

Operating Pressure

100 psi max @ 70° F

3" High Capacity Y-Strainer

FEATURES

- Heavy duty fiberglass-reinforced polypropylene
- Extra large 316 stainless steel screens-reinforced with polypropylene—available in 6, 12, 20 and 40 mesh
- EPDM gaskets standard
- 1/2" drain plug in bottom of cap

HIGH CAPACITY POLY Y-STRAINER

ITEM	DESCRIPTION	PART NO.	MESH
E	3" Y-Strainer	300A	6,12,20,40

NOTE: Please specify stainless steel mesh (6-12-20-40) 20 mesh is standard.

Operating Pressure

75 psi max @ 70° F

3" Quick Clean, High Capacity Y-Strainer

FEATURES

- Easy cleaning
- 4" reinforced nylon dust cap with patented safety latch
- 316 stainless steel screens - available in 1/16" or 1/8" perf
- EPDM gaskets standard

3" HIGH CAPACITY POLY Y-STRAINER

ITEM	DESCRIPTION	PART NO.	PERF
F	3" Y-Strainer w/4" Dust Cap	300A-ADC	1/16", 1/8"

NOTE: Please specify stainless steel perf (1/16", 1/8").

Operating Pressure

75 psi max @ 70° F



D



E



F

Price
Lookup

Price
Lookup

Price
Lookup

New

New

New

