

FOOD HANDLING

15 oz. White Nitrile COS

General-purpose food handling; assembly line and packaging belts; greaseproof; can be hot water and steam cleaned; resistant to food acids, fats and alkalis. Nitrile compound is also known as Buna-N and Hycar. Easy-to-clean, smooth 3/64" cover. FDA approved. Construction features tightly woven blend of cotton and polyester plies impregnated and covered with nitrile.

- 1** 2 Ply 15 oz. White Nitrile COS
- 2** 3 Ply 15 oz. White Nitrile COS
- 3** 4 Ply 15 oz. White Nitrile COS
- 4** 5 Ply 15 oz. White Nitrile COS



Poly White Nitrile COS

Very popular, high value, most generally used food belt available. High-strength polyester carcass has great dimensional stability for less stretch and better tracking. Mildew, rot, and deterioration resistant. Thin and flexible for small pulleys. Can be hot water and steam cleaned. FDA accepted.

- 5** 2 Ply Poly 60 White Nitrile COS
- 6** 3 Ply Poly 90 White Nitrile COS



Poly White Nitrile Heavy COS (RFL)

Thicker, stronger version of the Poly White Nitrile Series; features heavier, stronger polyester fabric RFL treated for greater adhesion under rugged conditions; also heavier skim coats between plies and a superior wear-resistant nitrile cover; usual advantages of 100% polyester carcass. Can be hot water and steam cleaned. FDA approved.

- 7** 2 Ply Poly 90 White Nitrile COS
- 8** 3 Ply Poly 135 White Nitrile COS



Poly White Nitrile 1/32" x 1/32"

Same basic construction as No. 8, but with a full bottom cover. This bottom cover provides extra wear resistance on roller conveyors. Both covers are easily cleaned. **Not for use on slider beds!** FDA approved.

- 8a** 3 Ply Poly 135 White Nitrile 1/32" x 1/32"



Poly White RMV COS

Super oil resistant RMV cover provides excellent animal and vegetable oil resistance at an economical price. Covers offer excellent resistance to staining. Belt features a durable 100% polyester carcass. Cleats can be welded to the belt surface. FDA approved.

- 8b** 2 Ply Poly 100 White RMV COS
- 8c** 3 Ply Poly 150 White RMV COS



Poly White Butyl COS

A specification designed for extreme temperature applications from -65° to 300°F. Recommended for high-heat uses such as heat sealing machines and heat (shrink) tunnels; also cold rooms and freezers. Allow 1% shrinkage in belt length when operated at temperatures over 275°F. Belt is FDA approved.

- 9** 3 Ply Poly 90 White Butyl COS



Poly White Teflon COS

Excellent for wet, sticky materials and operations involving gluing, coating, spreading; best release characteristics. The slippery top surface is created by the thin teflon film. Carcass is strong and flexible. FDA approved.

- 10** 3 Ply Poly 90 White Teflon COS
- 10a** 5 Ply CN40 White Teflon COS



BELT SAMPLES ARE AVAILABLE! CALL FOR DETAILS.