LIGHT DUTY/URETHANE BELTING

Brown Nitrile FBS

Features a tightly woven blend of cotton and polyester plies impregnated with nitrile, producing a belt suitable for light and medium-weight conveying for a multitude of applications. Particularly popular for oily conditions, especially the conveying of metal parts; also as carrying tapes for folding machines. Commonly used for power transmission belting in the heavier weights for conditions involving oil and heat. Economical. Very flexible.

24 3 Ply Brown Nitrile FBS

25 5 Ply Brown Nitrile FBS

26 7 Ply Brown Nitrile FBS

26a 9 Ply Brown Nitrile FBS



Poly Black Heavy-Duty Nitrile FBS

These belts are recommended for handling metal stampings, automotive parts, sheet steel, and any application requiring very high oil resistance. Features rugged, high-strength polyester carcass; is suitable for medium-capacity transmission belt where oil, grease or chemicals are present. Flexible, yet will withstand cutting, gouging, and abrasion.

27 4 Ply Poly 180 Black HD Nitrile FBS

28 5 Ply Poly 225 Black HD Nitrile FBS




4 Ply* Poly Black Neoprene FBS-SC

Static conductive properties allow this belt to be used in electronic parts conveying and for other products sensitive to static discharge.

*5 and 6 Ply are available. Minimum quantities apply.


27a 4 Ply Poly 180 Black Neoprene FBS-SC



Black Nitrile COS

An all-purpose conveyor belt with smooth nitrile top cover for assembly line, packaging and a wide variety of industrial uses. Flexible, yet strong, the 3 ply features a heavier carcass for added stretch resistance. 2 ply is 15 oz. cotton-polyester blend. Both have superior oil, grease, and animal fat resistance, and good heat capability.


29 2 Ply 15 oz. C-P Black Nitrile COS30 3 Ply Poly 135 Black Nitrile COS



Poly Black Checkout Belt

Designed for checkout counters for best appearance and maximum serviceability. Strong yet flexible; cover is nick-resistant; low friction bottom; very economical for light industrial uses.


31 2 Ply Poly 60 Black Checkout Belt



4 Ply Tan Sliptop

The hard-woven, abrasive-resistant bare nylon top surface is virtually frictionless and therefore ideal for "stall" operations or accumulating applications where the product must stop while the belt continues to move. Commonly used with automatic packaging machinery, and with gates or diverter arms.


32 4 Ply Tan Sliptop



Urethane #1200

This lightweight, economical urethane belt is an excellent value for applications requiring high resistance to cutting, gouging, tearing and high abrasion. In addition, both the cover and interwoven polyester carcass are resistant to most oils, greases, and chemicals. Will substantially outwear rubber-covered belt. FDA accepted.

33 Urethane #1200



BELT SAMPLES ARE AVAILABLE! CALL FOR DETAILS.



Call Toll Free: 1-866-711-4673
WebSales@GoodyearRubberProducts.com