


MORB-FP Straight 6405-O Series



PART NO. SIZE	TUBE O.D.	B1 SAE ORB	A2 NPTF	L LGTH	M.M.	W WIDTH	C HEX	C HEX	M.M.	Standard Material From Stock			
										S	FG	SS	B
6405-02-02-O	1/8	5/16-24	1/8-27	0.882	22.40	0.585	5/8	0.625	15.88	•			
6405-02-04-O	1/8	5/16-24	1/4-18	1.230	31.24	0.847	3/4	0.750	19.05	•			
6405-03-04-O	3/16	3/8-24	1/4-18	1.213	30.81	0.810	3/4	0.750	19.06	•			
6405-04-02-O	1/4	7/16-20	1/8-27	0.968	24.59	0.609	9/16	0.562	14.27	•			
6405-04-04-O	1/4	7/16-20	1/4-18	1.156	29.36	0.703	3/4	0.750	19.05	•		•	
6405-04-06-O	1/4	7/16-20	3/8-18	1.210	30.73	0.770	7/8	0.875	22.23	•		•	
6405-05-02-O	5/16	1/2-20	1/8-27	0.937	23.80	0.640	5/8	0.625	15.88	•		•	
6405-05-04-O	5/16	1/2-20	1/4-18	1.160	29.46	0.720	3/4	0.750	19.05	•		•	
6405-05-06-O	5/16	1/2-20	3/8-18	1.340	34.04	0.880	7/8	0.875	22.23	•			
6405-06-02-O	3/8	9/16-18	1/8-27	0.730	18.54	0.330	11/16	0.687	17.45	•			
6405-06-04-O	3/8	9/16-18	1/4-18	1.150	29.21	0.890	3/4	0.750	19.05	•		•	
6405-06-06-O	3/8	9/16-18	3/8-18	1.160	29.46	0.672	7/8	0.875	22.23	•		•	
6405-06-08-O	3/8	9/16-18	1/2-14	1.400	35.56	0.910	1 1/8	1.125	28.58	•		•	
6405-08-02-O	1/2	3/4-16	1/8-27	0.810	20.57	0.370	7/8	0.875	22.23	•		•	
6405-08-04-O	1/2	3/4-16	1/4-18	1.160	29.46	0.730	7/8	0.875	22.23	•		•	
6405-08-06-O	1/2	3/4-16	3/8-18	1.280	32.51	0.875	7/8	0.875	22.23	•		•	
6405-08-08-O	1/2	3/4-16	1/2-14	1.440	36.58	0.900	1 1/8	1.125	28.58	•		•	
6405-08-12-O	1/2	3/4-16	3/4-14	1.540	39.12	0.950	1 3/8	1.375	34.93	•		•	
6405-10-04-O	5/8	7/8-14	1/4-18	0.810	20.57	0.320	1	1.000	25.40	•		•	
6405-10-06-O	5/8	7/8-14	3/8-18	1.550	39.37	0.900	1 1/8	1.125	28.58	•		•	
6405-10-08-O	5/8	7/8-14	1/2-14	1.546	39.27	0.921	1 1/8	1.125	28.58	•		•	
6405-10-12-O	5/8	7/8-14	3/4-14	1.660	42.16	1.010	1 3/8	1.375	34.93	•		•	
6405-12-04-O	3/4	1 1/16-12	1/4-18	1.090	27.69	0.500	1 1/4	1.250	31.75	•		•	
6405-12-06-O	3/4	1 1/16-12	3/8-18	1.090	27.69	0.470	1 1/4	1.250	31.75	•		•	
6405-12-08-O	3/4	1 1/16-12	1/2-14	1.350	34.29	0.875	1 1/4	1.250	31.75	•		•	
6405-12-12-O	3/4	1 1/16-12	3/4-14	1.590	40.39	0.875	1 3/8	1.375	34.93	•		•	
6405-12-16-O	3/4	1 1/16-12	1-11 1/2	1.910	48.51	1.200	1 5/8	1.625	41.28	•		•	
6405-14-08-O	7/8	1 3/16-12	1/2-14	1.090	27.69	0.480	1 3/8	1.375	34.93	•		•	
6405-14-12-O	7/8	1 3/16-12	3/4-14	1.593	40.46	1.000	1 3/8	1.375	34.93	•		•	
6405-14-16-O	7/8	1 3/16-12	1-11 1/2	1.900	48.26	1.180	1 5/8	1.625	41.28	•		•	
6405-16-04-O	1	1 5/16-12	1/4-18	1.136	28.85	0.520	1 1/2	1.500	38.10	•		•	
6405-16-06-O	1	1 5/16-12	3/8-18	1.130	28.70	0.520	1 1/2	1.500	38.10	•		•	
6405-16-08-O	1	1 5/16-12	1/2-14	1.610	40.89	0.900	1 1/2	1.500	38.10	•		•	
6405-16-12-O	1	1 5/16-12	3/4-14	1.510	38.35	0.875	1 1/2	1.500	38.10	•		•	
6405-16-16-O	1	1 5/16-12	1-11 1/2	1.843	46.81	1.080	1 5/8	1.625	41.28	•		•	
6405-16-20-O	1	1 5/16-12	1 1/4-11 1/2	2.270	57.66	1.510	2	2.000	50.80	•		•	
6405-16-24-O	1	1 5/16-12	1 1/2-11 1/2	2.280	57.91	1.520	2 3/8	2.375	60.33	•		•	
6405-20-08-O	1 1/4	1 5/8-12	1/2-14	1.196	30.38	0.605	1 7/8	1.875	47.63	•		•	
6405-20-12-O	1 1/4	1 5/8-12	3/4-14	1.190	30.23	0.620	1 7/8	1.875	47.63	•		•	
6405-20-16-O	1 1/4	1 5/8-12	1-11 1/2	1.000	25.40	0.400	1 7/8	1.875	47.63	•		•	
6405-20-20-O	1 1/4	1 5/8-12	1 1/4-11 1/2	1.875	47.63	1.125	2	2.000	50.80	•		•	
6405-20-24-O	1 1/4	1 5/8-12	1 1/2-11 1/2	2.280	57.91	1.540	2 3/8	2.375	60.33	•		•	
6405-20-32-O	1 1/4	1 5/8-12	2-11 1/2	2.250	57.15	1.500	2 7/8	2.875	73.03	•		•	
NEW 6405-24-04-O										•			
6405-24-12-O	1 1/2	1 7/8-12	3/4-14	1.000	25.40	0.690	2 1/8	2.125	53.98	•		•	
6405-24-16-O	1 1/2	1 7/8-12	1-11 1/2	1.000	25.40	0.420	2 1/8	2.125	53.98	•		•	
6405-24-20-O	1 1/2	1 7/8-12	1 1/4-11 1/2	2.120	53.85	1.520	2 1/8	2.125	53.98	•		•	
6405-24-24-O	1 1/2	1 7/8-12	1 1/2-11 1/2	2.140	54.36	1.390	2 3/8	2.375	60.33	•		•	
6405-32-16-O	2	2 1/2-12	1-11 1/2	1.434	36.42	0.838	2 3/4	2.750	69.85	•		•	
6405-32-20-O	2	2 1/2-12	1 1/4-11 1/2	2.000	50.80	1.400	2 3/4	2.750	69.85	•		•	
6405-32-24-O	2	2 1/2-12	1 1/2-11 1/2	2.000	50.80	1.400	2 3/4	2.750	69.85	•		•	
6405-32-32-O	2	2 1/2-12	2-11 1/2	2.240	56.90	1.640	2 7/8	2.875	73.03	•		•	