

R-5½ Rivet Fasteners are used on belts from ⅜" to 1½" and 800 PIW. Hinge pins are found on pages 20-21. Riv-Nail selection is found on pages 16-17.

STEEL R-5½ RIVET FASTENER

NUMBER	PRICE
R-5½-24	\$ 29.42
R-5½-30	36.20
R-5½-36	45.24
R-5½-42	52.04
R-5½-48	61.08
R-5½-54	67.86
R-5½-60	76.90
R-5½-72	92.74

HIGH-CHROME STAINLESS RC-5½ RIVET FASTENER

NUMBER	PRICE
RC-5½-24	\$ 49.08
RC-5½-30	60.42
RC-5½-36	75.52
RC-5½-42	86.86
RC-5½-48	101.92
RC-5½-54	113.26
RC-5½-60	128.38
RC-5½-72	170.26

R-6 Rivet Fasteners are used on belts from 1½" to ¾" and up to 1000 PIW. Hinge pins are found on pages 20-21. Riv-Nail selection is found on pages 16-17.

STEEL R-6 RIVET FASTENER

NUMBER	PRICE
R-6-24	\$ 38.80
R-6-30	47.78
R-6-36	59.72
R-6-42	68.64
R-6-48	80.60
R-6-54	89.54
R-6-60	101.50
R-6-72	122.38

HIGH-CHROME STAINLESS RC-6 RIVET FASTENER

NUMBER	PRICE
RC-6-24	\$ 65.68
RC-6-30	79.96
RC-6-36	94.24
RC-6-42	114.62
RC-6-48	134.50
RC-6-54	149.46
RC-6-60	169.38
RC-6-72	204.26

RC-8 Rivet Fasteners

are used on belts from 1½" to ¾" and up to 1500 PIW. Hinge pins are found on pages 20-21. Riv-Nail selection is found on pages 16-17.

HIGH-CHROME STAINLESS RC-8 RIVET FASTENER

NUMBER	PRICE
RC-8-48	\$ 147.96
RC-8-54	164.42
RC-8-60	186.34
RC-8-72	224.68
RC-8-84	262.44

SELECTING SIZE AND METALS

Rivet Hinge fasteners are available in R-3, R-5, R-5½, R-6, and R-8 sizes which fit belts ⅜" - ¾". The fastener strip is cross-scored so it can be easily broken by hand to fit any belt width. Fastener strips are packaged as one set per carton. Hinge pin and Riv-Nail selection is according to belt thickness and style. These are sold separately.

RIVET HINGE SPECIFICATIONS

PULLEY DIAMETER	BELT THICKNESS	PIW	SIZE
6"	⅜" - ⅝"	330	3
9"	7/32" - 7/16"	450	5
12"	⅜" - 1½/32"	800	5½
18"	1¾/32" - ¾"	1000	6
18"	15/32" - ¾"	1500	8

STEEL Conveyor Accessories, Inc. uses a special grade of high strength steel which has been annealed. This special grade yields 25 to 35% greater tensile strength and has higher hardness for longer life, compared to some other steel fasteners. R-5 and R-6 are zinc coated "silver," whereas R-3 and R-5½ are zinc coated with zinc dichromate to give it a "gold" color for easy identification.

STAINLESS STEEL A high chrome stainless steel was selected for applications which are either corrosive or abrasive. The chrome in the CAI fastener is about 50% greater than some other belt fastener products. This gives our product greater corrosion resistance which will yield longer life. Also, this grade of stainless yields about 25 to 30% higher tensile strength. This material is designated "RC" and is magnetic. The non-magnetic grade is designed "RS."