

TETRAGLAS® 3000 BRAIDED TUBING

TETRAGLAS® 3000 Braided Tubing is a texturized silica tubing for service temperatures to 2300°F.

Standard wall thickness is 1/16" thk.
1/8" thk. available upon request.

- Feet per carton: +/- 10%
- API 16D Approved
- Sold in Full Carton Quantities Only.

SIZE	FT/CTN
3/8	1400
1/2	1000
5/8	900
3/4	750
7/8	650
1	500
1-1/4	450
1-1/2	350
1-3/4	300
2	250
2-1/2	225
3	200
3-1/2	190
4	175
5	120



SILICONE COATED TETRAGLAS® TUBING

Our Silicone Coated Knitted and Braided Tetraglas® Tubing is manufactured from low density, high bulk fiberglass then coated with standard red silicone rubber coating. This product is designed to protect wires, hoses and cables from hazards of high heat and occasional flame.

Wall Thickness: 1/8"

Available Inside Diameter: 3/8", 7/16", 1/2", 5/8", 3/4", 7/8", 1", 1-1/8", 1-1/4", 1-3/8", 1-1/2", 1-5/8", 1 3/4", 2", 2-1/4", 2-1/2", 2-3/4", 3", 3-1/4", 3-1/2", 3-3/4", 4", 4-1/2", 5"

Various applications include:

- Protects continuously from -65°F to +500°F with excursions to 700°F
- Protection from molten splash
- Allows qualified hose assemblies to pass the SAE Aerospace standards 1055B testing under stated flow and pressure conditions
- This product offered in standard 100 ft. length only.

