

NO WIRE TETRAGLAS-T® 500

This is a fabric made from texturized fiberglass yarn which is coated and impregnated with a white rubber compound. This gasket material is used where rough or uneven flanges need a sealing material. For applications ranging from 300°F to 550°F.

- Weight = 5 lbs/yd for 1/16" thk.
- Weight and length tolerance: +/- 10%
- Available with Frictioned Tacky, Dusted (both sides), Graphited (both sides), or Red & Black coating.
- Less than full roll quantities are available.

THICKNESS & WIDTH	YDS/ROLL
1/16 X 40	50
1/8 X 40	25
3/16 X 40	16.67
1/4 X 40	12.50

WIRE INSERTED TETRAGLAS-T® 500

This is a fabric made from a different type of fiberglass yarn which has been twisted with a brass wire for additional strength and density when fabricated into boiler gaskets, groove packing, tapes, etc. This is our latest in a long line of asbestos replacement products.

All fabricated TETRAGLAS-T® products will be made by Darco from this product. For applications ranging from 300°F to 550°F.

- Weight = 5 lbs/yd for 1/16" thk.
- Weight and length tolerance: +/- 10%
- Available with Frictioned Tacky, Dusted (both sides), Graphited (both sides), or Red & Black coating.
- Less than full roll quantities are available.

THICKNESS & WIDTH	YDS/ROLL
1/16 X 40	50
1/8 X 40	25
3/16 X 40	16.67
1/4 X 40	12.50