

WIRE INSERTED TETRAGLAS-T® FOLDED TAPE

A general utility tape used for steam, air, water and ammonia. Particularly useful on rough or uneven flanges.

Manufactured from texturized fiberglass yarns into Tetraglas® cloth, frictioned with natural or SBR rubber or a blend of the two.

For service temperatures to 550°F constant.

- Available thicknesses: 1/16", 1/8", 3/16", 1/4", & 3/8"
- Available widths: 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 3", 4", & 5"
- Standard roll: 25' or 50' lengths
- Non-standard lengths & widths also available



WIRE INSERTED TETRAGLAS-T® LUTING & GROOVE PACKING

Darco Southern, Inc. manufactures luting and groove packing from the same high quality TETRAGLAS-T® cloth that is used in the manufacture of its other folded products.

Plain Tetraglas® cloth is frictioned with a blend of natural or SBR rubber compound from which the packing sizes are carefully formed in solid construction and squared to accurate dimensional size.

Finished packing has a light talc dusting and is supplied in standard 25 ft. lengths, coil form. For use as an alternative to asbestos luting and groove packing for door gasketing at temperatures to 550°F.

Available Styles: Solid Roll-Up

Also available:

- Surface graphite
- Rectangular cross section & custom cross section also available

*Ask your Customer Service Rep. about Endless Luting Gaskets



SIZE	LBS/100FT
3/8	10.6
7/16	15.6
1/2	20.0
9/16	25.0
5/8	28.7
1-1/16	35.0
3/4	42.0
1-3/16	49.0
7/8	55.0
1	70.0
1-1/8	80.0
1-1/4	100.0
1-3/8	115.0
1-1/2	145.0
2	260.0

