# **-**

### Dry Quick Disconnects

## **Dry Quick Disconnect Couplers**

(Hose Unit)

- Coupler has built-in swivel
- Stainless steel ball bearings
- Shaft journal in stainless steel embedded in PTFE (Teflon®) to eliminate seizure
- Riveted piston pin to minimize the risk for failure under extreme pressure conditions
- Protecting ring is weather resistant rubber Electrically conductive

- All wetted parts are stainless steel
- Rollers for the stainless steel units are hastelloy C276 on the stainless steel shaft
- Rollers for the aluminum and brass units are aluminum-bronze on the stainless steel shaft
- Plugs in composite (Polyeten PE-HD 300) provide a very good protection against corrosion, and withstand both hot and cold environments

### Dry Quick Disconnect Couplers x Female NPT with Viton® seals



11/2" and 2"



3" and 4"

Female	Body	316 Stainles	s Steel	Anodized Alu	uminum	Brass / Gur	nmetal
NPT	Size	Part #	Price/E	Part #	Price/E	Part #	Price/E
3/4"	56 mm	DDC075SS	\$1994.00	DDC075AL	\$1041.10	DDC075BR	\$1484.55
1"	56 mm	DDC100SS	1994.00	DDC100AL	1041.10	DDC100BR	1484.55
11/2"	70 mm	DDC150SS	3357.20	DDC150AL	1404.00	DDC150BR	1740.75
2"	70 mm	DDC200SS	3357.20	DDC200AL	1404.00	DDC200BR	1740.75
3"	105 mm	DDC300SS105	5174.80	DDC300AL105	1560.00	DDC300GM105	2328.60
3"	119 mm	DDC300SS	5202.00	DDC300AL	1573.50	DDC300GM	2607.40
4"	164 mm	DDC400SS	9044.00	DDC400AL	3435.20	DDC400GM	4800.00
6"	238 mm	DDC600SS	20600 00	DDCGOOAL	15200 00		

### **Composite Dust Plugs for Couplers**



Size	Body Size	Part #	Price/E
3/4" and 1"	56 mm	DDDP075	\$98.40
1½" and 2"	70 mm	DDDP150	101.80
3"	105 mm	DDDP300105	105.20
3"	119 mm	DDDP300	105.20
4"	164 mm	DDDP400	210.30
6"	238 mm	DDDP600 *	575.60

<sup>\* 6&</sup>quot; dust plug is aluminum

62 DPL108

