

# Air King 4 - Lug Quick-Acting Couplings

| 0:      | Iron        |                      | Brass           |                     | Pkg | Hose Ends           |  |
|---------|-------------|----------------------|-----------------|---------------------|-----|---------------------|--|
| Size    | Part #      | Price/E              | Part #          | Price/E             | Qty |                     |  |
| 1¼"     | AM16        | \$22.80              | AB16            | \$60.40             | 25  |                     |  |
| 11⁄2"   | AM21        | 22.70                | AB21            | 58.00               | 25  |                     |  |
| 2"      | AM26        | 33.90                | AB26            | 77.85               | 10  |                     |  |
| 0:      |             | Iron                 | Br              | ass                 | Pkg | Female NPT Ends     |  |
| Size    | Part #      | Price/E              | Part #          | Price/E             | Qty |                     |  |
| 1¼"     | AM18        | \$22.80              | AB18            | \$69.20             | 25  |                     |  |
| 1½"     | AM23        | 22.25                | AB23            | 60.40               | 25  | N. BETTER           |  |
| 2"      | AM28        | 26.90                | AB28            | 72.60               | 20  | - And and a second  |  |
| Washers | s for 4-Lug | • Rated to 150 PSI   |                 | -                   |     |                     |  |
| Rı      | ubber       |                      | ommended. See p | 0                   |     | SAFETY Optional Pkg |  |
| Part #  | Price/E     | Warning: Must use    |                 |                     |     | ALERT Optional Pkg  |  |
| AWR14   | \$3.90      | Note: Safety clips a |                 | otri 2-lug and 4-li | Jg  | QIY SHOWN           |  |

Universal Couplings. See page 94.

### **Sand Blast Couplings**

Sand blast couplings are designed for use on sand blast hose.

Supplied with screws

Nozzle holders have 1¼" NPSM thread.

 Rated to 110 PSI Installation: 1) Er

- : 1) Ends of hose must be cut square to fit snug against metal end.
  - 2) Holding hose tight to end of fitting, insert screws and turn in full, putting screw 180° from first to ensure best centering.
  - 3) After all screws have been placed, check tube opposite screws to be sure screws have not penetrated completely through.
  - 4) On quick couplings, insert safety clips

Note: Abrasive blasting equipment must have hose safety cables (page 104) or hose coupling safety locks.

|        |         | Quick Couplings |         |          |         |  |
|--------|---------|-----------------|---------|----------|---------|--|
| Hose   | Hose    | Brass           |         | Aluminum |         |  |
| Size   | O.D.    | Part #          | Price/E | Part #   | Price/E |  |
| 3/4"   | 1-1/2"  | BSB75           | \$27.65 | ASB75    | \$12.05 |  |
| 1"     | 1-7/8"  | BSB100          | 24.10   | ASB100   | 13.00   |  |
| 1-1/4" | 2-5/32" | BSB125          | 43.00   | ASB125   | 22.20   |  |
| 1-1/2" | 2-3/8"  | BSB150          | 59.35   | ASB150   | 26.55   |  |

## Nozzle Holders

| Hose   | Hose    | Brass  |         | Aluminum |         |
|--------|---------|--------|---------|----------|---------|
| Size   | O.D.    | Part # | Price/E | Part #   | Price/E |
| 3/4"   | 1-1/2"  | BNH75  | \$22.00 | ANH75    | \$10.80 |
| 1"     | 1-7/8"  | BNH100 | 32.45   | ANH100   | 12.00   |
| 1-1/4" | 2-5/32" | BNH125 | 36.60   | ANH125   | 16.35   |
| 1-1/2" | 2-3/8"  | BNH150 | 64.95   | ANH150   | 21.70   |

#### **Threaded Couplings**

| NPT  | Bra    | ass     | Aluminum |         |  |
|------|--------|---------|----------|---------|--|
| Size | Part # | Price/E | Part #   | Price/E |  |
| 1¼"  | BSC125 | \$30.05 | ASC125   | \$12.60 |  |
| 1½"  | BSC150 | 30.05   | ASC150   | 12.60   |  |



oducts.com

#### **Replacement Gaskets Replacement Screws** Price/E Black Nitrile Urethane Part # Part # Price/E Part # Price/E SBCS \$.25 SBG \$.80 USBG \$3.20

WebSales@GoodyearRubberPr

-866

DPL108



91

We Ship

World Wide

D