

-

Dix-Lock Quick Acting Couplings

- It takes a minimum of 5 PSI to get a positive seal
 Dix-Lock is rated to 300 PSI

| Body Size | NPT Thread Size | Material | Part # | Price/E | Pkg Qty | Male Head x Female NPT End | |
|--------------|--------------------|-----------------|----------|---------|------------|---|-----------------|
| 1/2" | 3/8" | plated steel | QM81 | \$21.24 | 25 | | |
| 1/2" | 1/2" | plated steel | QM82 | 21.24 | 25 | | |
| 1/2" | 3/4" | plated steel | QM83 | 21.24 | 25 | | |
| 1/2" | 1" | plated steel | QM85 | 23.50 | 25 | | _ |
| 1/2" | 3/8" | brass | QB81 | 35.45 | - 20 | | D |
| 1/2" | 1/2" | brass | QB82 | 35.45 | | | - |
| 1/2" | 3/4" | brass | QB83 | 35.45 | | | Air Fittings |
| 1/2" | 1" | brass | QB85 | 37.01 | 25 | | Air 1gs |
| 1/2" | 3/4" | stainless steel | QSS83 | 76.31 | - | | |
| 1-1/4" | 1" | brass | QB87 | 125.93 | 10 | | |
| 1-1/4" | 1-1/4" | brass | QB89 | 188.22 | 10 | | |
| , . | , . | | 4200 | | | | |
| Body | NPT Thread | | _ | | Pkg | | |
| Size | Size | Material | Part # | Price/E | Qty | Female Head x Female NPT End | |
| 1/2" | 3/8" | plated steel | QM101 | \$17.21 | 25 | | |
| 1/2" | 1/2" | plated steel | QM102 | 17.21 | 25 | | |
| 1/2" | 3/4" | plated steel | QM103 | 17.21 | 25 | | |
| 1/2" | 3/4" | plated steel | QM103V * | 30.13 | 25 | | |
| 1/2" | 1" | plated steel | QM105 | 18.96 | 25 | | |
| 1/2" | 3/8" | brass | QB101 | 27.28 | - | La | |
| 1/2" | 1/2" | brass | QB102 | 27.28 | - | | |
| 1/2" | 3/4" | brass | QB103 | 27.28 | - | 12 States | |
| 1/2" | 1" | brass | QB105 | 29.95 | 25 | a free of the | |
| 1/2" | 3/4" | stainless steel | QSS103 | 76.31 | - | | |
| 1-1/4" | 1" | brass | QB107 | 100.27 | 10 | | |
| 1-1/4" | 1-1/4" | brass | QB109 | 138.89 | 10 | | |
| * valve | d coupler not | shown | | - | - | | |

Optional Pkg./Box Quantity Shown

| Body I Size | Hose Shank Size | Material | Part # | Price/E | Male Locking Head x Hose Shank |
|----------------|--------------------|--------------|--------|---------|--------------------------------|
| 1/2" | 1/2" | plated steel | QM33 | \$29.09 | |
| 1/2" | 3/4" | plated steel | QM44 | 29.09 | |
| 1/2" | 1/2" | brass | QB33 | 41.34 | |
| 1/2" | 3/4" | brass | QB44 | 41.34 | |
| .,_ | 0, 1 | | | | |

| Body Size | NPT Thread Size | Material | Part # | Price/E | Male Locking Head x Male NPT |
|--------------|--------------------|--------------|--------|---------|------------------------------|
| 1/2" | 1/2" | plated steel | QM66 | \$29.09 | |
| 1/2" | 3/4" | plated steel | QM88 | 29.09 | |
| 1/2" | 1/2" | brass | QB66 | 41.34 | |
| 1/2" | 3/4" | brass | QB88 | 41.34 | |

Positive safety lock

With locking nut in place sleeve cannot be moved to open coupling.

Dix-Lock Gaskets

Call Toll Free: 1-866-711-4673

WebSales@GoodyearRubberProducts.com

| Body | Βι | na-N | |
|--------|--------|---------|--|
| Size | Part # | Price/E | |
| 3/8" | QBM1 | \$1.31 | |
| 1/2" | QBM2 | 1.31 | |
| 1-1/4" | QBM3 | 7.12 | |

DPL108



99

We Ship

World Wide