



Air Fittings and Accessories

Air Chief Industrial Interchange Quick-Connect Couplers

Air Chief industrial quick-connect couplers are of the popular Industrial Interchange design and will interchange with many other makes. Couplers shut-off when disconnected.

- Rated to **300 PSI**
- Temperature range - **40°F to 250°F**
- *For air service only*
- Interchanges with MIL Spec. MIL-C-4109F/A-A-59439

D
Air Fittings

Female Pipe Thread	Body Size	NPT Thread Size	Material	Flow Rating at 100 PSI	Part #	Price/E	Pkg Qty
	Semi-Automatic Pull sleeve to connect						
	1/4"	1/8"	brass	37 CFM	DC2021	\$11.95	10
	1/4"	1/4"	brass	37 CFM	DC20	7.85	10
	1/4"	3/8"	brass	37 CFM	DC2023	10.75	10
	3/8"	1/4"	steel	70 CFM	DC2622	16.55	10
	3/8"	3/8"	steel	70 CFM	DC26	15.60	10
	3/8"	1/2"	steel	70 CFM	DC2624	19.85	10
	1/2"	3/8"	steel	150 CFM	DC1023	22.75	10
	1/2"	1/2"	steel	150 CFM	DC10	21.30	10
	1/2"	3/4"	steel	150 CFM	DC1026	27.80	10
	3/4"	1/2"	brass	200 CFM	DC7024 *	57.20	1
	3/4"	3/4"	brass	200 CFM	DC7026 *	58.50	1
	3/4"	1"	brass	200 CFM	DC7028 *	61.80	1
	1/4"	1/4"	303 stainless	37 CFM	DC20S	38.57	5
	3/8"	3/8"	303 stainless	70 CFM	DC26S	55.53	5
	1/2"	1/2"	303 stainless	150 CFM	DC10S	85.75	5

* 3/4" are automatic sleeve

Male Pipe Thread	Body Size	NPT Thread Size	Material	Flow Rating at 100 PSI	Part #	Price/E	Pkg Qty
	Semi-Automatic Pull sleeve to connect						
	1/4"	1/8"	brass	37 CFM	DC2101	\$10.05	10
	1/4"	1/4"	brass	37 CFM	DC21	8.30	10
	1/4"	3/8"	brass	37 CFM	DC2103	9.95	10
	3/8"	1/4"	steel	70 CFM	DC2502	15.55	10
	3/8"	3/8"	steel	70 CFM	DC25	16.10	10
	3/8"	1/2"	steel	70 CFM	DC2504	19.30	10
	1/2"	3/8"	steel	150 CFM	DC903	21.05	10
	1/2"	1/2"	steel	150 CFM	DC9	18.75	10
	1/2"	3/4"	steel	150 CFM	DC906	25.10	10
	3/4"	1/2"	brass	200 CFM	DC7104 *	57.20	1
	3/4"	3/4"	brass	200 CFM	DC7106 *	58.50	1
	3/4"	1"	brass	200 CFM	DC7108 *	60.50	1
	1/4"	1/4"	303 stainless	37 CFM	DC21S	37.35	5
	3/8"	3/8"	303 stainless	70 CFM	DC25S	65.88	5
	1/2"	1/2"	303 stainless	150 CFM	DC9S	95.29	5

* 3/4" are automatic sleeve

Optional Pkg./Box Quantity Shown