


## Air Fittings and Accessories

### Mini In-Line Lubricators

- Can be refilled under line pressure
- Oil capacity is ¼ fluid ounce
- Flow rating is 22 SCFM at 100 PSIG
- Maximum operating conditions: **200 PSIG** and **175°F**


Female NPT Inlet	NPT Outlet	Aluminum	
		Part #	Price/E
1/4"	1/4" female	<b>ML200</b>	<b>\$67.20</b>
1/4"	1/4" male	<b>ML200M</b>	<b>68.00</b>
3/8"	3/8" male	<b>ML300M</b>	<b>68.00</b>



### Mini In-Line Filter

- Flow rating is 17 SCFM inlet pressure at 100 PSIG
- Maximum operating conditions: **200 PSIG** and **175°F**
- Either port may be used as an inlet port
- Filter element rated at 5 microns

Female NPT	Male NPT	Aluminum	
		Part #	Price/E
1/4"	1/4"	<b>MF200</b>	<b>\$40.25</b>
Description		Part #	Price/E
Replacement element		<b>FRP-95-199</b>	<b>\$12.90</b>



**D**  
Air Fittings

### In-Line Air Filters

Designed specifically for the protection of small air tools, such as impact wrenches, nut runners, grinders and screwdrivers. The all-anodized, lightweight aluminum housing is compact can be used directly before the air tool.

- Maximum operating pressure: **500 PSI**
- Operating temperatures: **35°F** to **200°F**
- Air flow is 140 SCFM
- Standard element is 40 micron, which ensures minimum pressure drop
- Elements can be replaced quickly

Male NPT	Overall Length	Diameter	Weight Lbs.	Aluminum	
				Part #	Price/E
3/4"	3-13/16"	1-1/2"	.46	<b>9076M</b>	<b>\$63.00</b>



### Miniature Non-Repairable General Purpose Regulators

- Relieving piston design allows reduction of downstream pressure when the system is dead-ended.
- Reliable pressure regulation at air flows up to 13 SCFM
- Left to right flow
- 5 to 125 PSIG outlet pressure adjustment range
- Compact design and light weight construction
- Wrench flats for easy installation
- Model supplied with a GC620 gauge

With Gauge			Without Gauge		
Size	Part #	Price/E	Size	Part #	Price/E
1/4"	<b>R46-200RG</b>	<b>\$50.20</b>	1/4"	<b>R46-200R</b>	<b>\$35.75</b>



### Air Tool Lubricants

A specially formulated high grade lubricant that prolongs the service life of air tools, cylinders and accessories while permitting maximum performance. Prohibits rust and removes moisture as it lubricates. It is non-corrosive, non-reactive and does not decompose. This compound is superior in performance to ordinary lubricants. The easy pour spout helps prevent costly spills. #10 weight. Use with the in-line lubricators on page 103.

Size	Part #	Price/E	Pkg Qty
1 pint	<b>DATL016</b>	<b>\$10.10</b>	12
1 gallon	<b>DATL128</b>	<b>51.00</b>	4

Optional Pkg./Box Quantity Shown



1 gallon



1 pint