

Air Chief Safety Blow Gun

This basic safety blow gun is designed to conform to OSHA Standard 1910.242 (B) permitting a maximum of 30 PSI outlet pressure when dead ended based on a maximum of 150 PSI inlet pressure as well as OSHA Standard 1910.95 regulating occupational noise level exposure. *Safety glasses or shield must be worn when using any blow gun.*



- Blow gun body is designed to comfortably fit the contour of the hand, minimizing user fatigue.
- Large lever with black vinyl grip further adds to the ergonomic design and allows for easy air flow activation.
- Chrome plated zinc die cast body, nickel plated steel lever, vinyl thumb grip, stainless steel spring, brass valve, Buna-N seals and nickel plated brass tip combine for superior corrosion resistance as well as a contemporary look.
- ¼" female NPT inlet
- Recessed internal slotted screw allows easy access to valve assembly for repairs or replacement.

Part #	Price/E
D204-30	

**SAFETY
ALERT**

Note: The Air Chief safety blow gun has a safety tip which prevents buildup of tip pressure in the event the outlet is obstructed or "dead ended". It complies with the requirements for OSHA 1910.242(B) and 1910.95 when used on air lines of 150 PSI or less.

Premium Safety Blow Gun

The premium safety blow gun features a distinctive black powder coat finish to give it a rich appearance as well as long term protection from corrosion and rough handling. Designed to conform to OSHA Standard 1910.242 (B) permitting a maximum of 30 PSI outlet pressure when dead ended based on a maximum of 150 PSI inlet pressure as well as OSHA Standard 1910.95 regulating occupational noise level exposure. *Safety glasses or shield must be worn when using any blow gun.*



- Blow gun body is designed to comfortably fit the contour of the hand, minimizing user fatigue.
- Large lever with vinyl grip further adds to the ergonomic design and allows for easy air flow activation.
- Zinc die cast body with a black powder coat finish, nickel plated steel lever, vinyl thumb grip, stainless steel spring, brass valve, Buna-N seals and nickel plated brass tip.
- ¼" female NPT inlet

Part #	Price/E
D204-30P	

**SAFETY
ALERT**

Note: The premium safety blow gun has a safety tip which prevents buildup of tip pressure in the event the outlet is obstructed or "dead ended". It complies with the requirements for OSHA 1910.242(B) and 1910.95 when used on air lines of 150 PSI or less.