

Safety Air Booster Blow Gun

The multiple holes in the safety booster tip of the safety air booster gun create a venturi effect that increases air flow (working capacity) while still remaining compliant with OSHA Standard 1910.242 (B). *Safety glasses or shield must be worn when using any blow gun.*

- Blow gun body is designed to comfortably fit the contour of the hand, minimizing user fatigue.
- Large lever with vinyl grip further adds to the ergonomic design and allows for easy air flow activation.
- Chrome plated zinc die cast body, nickel plated steel lever, vinyl thumb grip, stainless steel spring, brass valve, Buna-N seals and nickel plated brass Safety Booster tip.
- ¼" female NPT inlet



D
Air
Fittings

Part #	Price/E
D204-30SB	\$20.75

Note: The safety air booster blow gun has a safety tip which prevents buildup of tip pressure in the event the outlet is obstructed or "dead ended". It complies with the requirements for OSHA 1910.242(B) and 1910.95 when used on air lines of 150 PSI or less.

SAFETY
ALERT

Non-Safety Brass Tip Blow Gun

The ventless, nickel-plated tip provides the most economical means of achieving a concentrated stream of air for many blow-off applications. All other components and design features are the same as our Air Chief safety blow gun (D204-30). *Must be used on air lines having a maximum regulated pressure of 30 PSI in order to comply with OSHA Standard 1910.242 (B).*

- Blow gun body is designed to comfortably fit the contour of the hand, minimizing user fatigue.
- Large lever with vinyl grip further adds to the ergonomic design and allows for easy air flow activation.
- Chrome plated zinc die cast body, nickel plated steel lever, vinyl thumb grip, stainless steel spring, brass valve, Buna-N seals and ventless, nickel plated brass tip provide superior corrosion resistance.
- ¼" female NPT inlet



Part #	Price/E
D605	\$14.75

Caution: This blow gun **does not** have a safety by-pass to prevent buildup of tip pressure in the event of tip blockage. It may be used for cleaning purposes only if the air supply (inlet pressure) has been reduced to 30 PSI or less.

SAFETY
ALERT

Non-Safety Rubber Tipped Blow Gun

The rubber tip will not scratch or mar delicate surfaces. The conical, rubber tip can also be used to create a seal between the blow gun and fluid lines (or any other opening). Base of the tip is nickel-plated brass for additional corrosion resistance. *Must be used on air lines having a maximum regulated pressure of 30 PSI in order to comply with OSHA Standard 1910.242 (B).*

- Blow gun body is designed to comfortably fit the contour of the hand, minimizing user fatigue.
- Large lever with vinyl grip further adds to the ergonomic design and allows for easy air flow activation.
- Chrome plated zinc die cast body, nickel plated steel lever, vinyl thumb grip, stainless steel spring, brass valve, Buna-N seals and rubber tip with a nickel plated brass base provide superior corrosion resistance.
- ¼" female NPT inlet



Part #	Price/E
D201	\$19.35

Caution: This blow gun **does not** have a safety by-pass to prevent buildup of tip pressure in the event of tip blockage. It may be used for cleaning purposes only if the air supply (inlet pressure) has been reduced to 30 PSI or less.

SAFETY
ALERT