Air Fittings and Accessories

Polyurethane Air Hose

Fittings Included

Lighter in weight than ordinary rubber hose. A sturdy, nylon-reinforced braid between the inner and outer tube allows for a higher working pressure.





- Durable
- Lightweight
- Excellent flexibility
- Oil resistant
- Durometer: Shore A 85
- Temperature range: -40°F to 155°F
- Working pressure at 70°F: 210 PSI

Hose I.D.	Length	Male NPT	Part #	Price/E
1/4"	50'	1/4"	450-4S	\$67.30
3/8"	50'	1/4"	650-4S	130.00
3/8"	50'	3/8"	650-6S	140.00

Coil-Chief Self-Storing Air Hose Fittings Included

Bulk Hose - No Fittings

Hose I.D. Length Part # Price/I	Æ
1/4" 100' CC14100B * \$82.2 3/8" 100' CC38100B * 171.1 1/2" 100' CC12100B * 293.5	10

* Bulk hose needs assembly kits for ends



- · Coil-Chief comes standard with swivel on one end
- Yellow

Repair Kits

Hose I.D.	Length	Male NPT	Part #	Price/E
1/4"	12'	1/4"	CC1412	\$21.90
1/4"	25'	1/4"	CC1425	30.50
1/4"	50'	1/4"	CC1450	54.00
3/8"	25'	3/8"	CC3825	52.80
3/8"	50'	3/8"	CC3850	93.00
1/2"	25'	1/2"	CC1225	106.70
1/2"	50'	1/2"	CC1250	162.30

Size	Type	Part #	Price/E
1/4"	rigid male	RK090	\$6.60
1/4"	swivel male	RK092	8.80
3/8"	rigid male	RK110	9.20
3/8"	swivel male	RK112	12.50
1/2"	rigid male	RK118	19.55
1/2"	swivel male	RK119	22.40

- Repair/assembly kits include rigid or swivel male fittings, nut, insert, ferrule and spring guard.
- Nylon working pressure: 200 PSI at 70°F

Polyurethane Self-Storing Air Hose

Fittings Included

- · Extremely flexible resists kinking
- Impervious to abrasions, heat and oil
- Superior elasticity and coil memory

- Both ends swivel
- Blue
- Polyurethane working pressure: 125 PSI at 70°F



Repair Kits

Hose I.D.	Length	Male NPT	Part #	Price/E
1/4"	10'	1/4"	PU1410	\$35.75
1/4"	15'	1/4"	PU1415	41.20
1/4"	25'	1/4"	PU1425	49.40
3/8"	15'	3/8"	PU3815	67.30
3/8"	20'	3/8"	PU3820	82.50
3/8"	25'	3/8"	PU3825	94.10
3/8"	50'	3/8"	PU3850	190.25
1/2"	15'	1/2"	PU1215	132.30

Tubing I.D.	g Size O.D.	Size	Туре	Part #	Price/E
1/4" 3/8"	3/8" 9/16"	1/4" 1/4"	swivel male swivel male		\$9.90 12.25

128 DPL108