


## Series 1 Lubricators - Micro-Fog, Pyrex® Sight Feed Domes

- Designed for use with alcohol or other anti-freeze agents when units are installed in cold temperature environments.
- Pyrex® sight feed dome with aluminum case and fluorocarbon O-Rings and seals; Pyrex® sight glass on bowls and metal petcock drain.
- Micro-fog lubricators, identified by a red adjusting screw, are used for applications containing one or more points of lubrication, cylinders and multiple or single tools.
- Air flow through the lubricator lifts oil from the reservoir to the sight-feed dome. Oil is dropped into the fog generator and atomized into a fine mist. Lightweight particles are delivered downstream for lubrication. Heavier particles fall back into the reservoir.
- The micro-fog lubricator delivers 10% of the oil drops visible through the transparent sight-feed dome.
- Micro-fog lubricators *cannot* be filled under pressure.




### 1/4" Basic Metal Bowl with Sight Glass

Size	Part #	SCFM	Price/E
1/4"	<b>L72M-2MBPX</b>	51	<b>\$226.05</b>
3/8"	<b>L72M-3MBPX</b>	51	<b>194.60</b>

- 2 oz. reservoir
- In-line or modular installation
- Micro-fog design delivers aerosol mist.
- Quick release bayonet bowl
- Inlet pressure for metal bowl is **250 PSI**
- Maximum temperature for metal bowl is **175°F**
- Recommended lubricants: Use a misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at **100°F**




D  
Air  
Fittings



### 3/8" Basic Metal Bowl with Sight Glass

Size	Part #	SCFM	Price/E
1/4"	<b>L73M-2MBPX</b>	60	<b>\$207.35</b>
3/8"	<b>L73M-3MBPX</b>	60	<b>224.80</b>
1/2"	<b>L73M-4MBPX</b>	60	<b>224.80</b>


- 4 oz. reservoir
- In-line or modular installation
- Micro-fog design delivers aerosol mist
- Quick release bayonet bowl
- Inlet pressure for metal bowl is **250 PSI**
- Maximum temperature for metal bowl is **175°F**
- Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at **100°F**



### 1/2" Basic Metal Bowl with Sight Glass

Size	Part #	SCFM	Price/E
3/8"	<b>L74M-3MBPX</b>	114	<b>\$274.20</b>
1/2"	<b>L74M-4MBPX</b>	154	<b>274.20</b>
3/4"	<b>L74M-6MBPX</b>	142	<b>274.20</b>

- 7 oz. reservoir
- In-line or modular installation
- Micro-fog design delivers aerosol mist
- Quick release bayonet bowl
- Inlet pressure for metal bowl is **250 PSI**
- Maximum temperature for metal bowl is **175°F**
- Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at **100°F**



### 1/2" Basic Metal Bowl with Sight Glass

Size	Part #	SCFM	Price/E
3/4"	<b>L17-600APX</b>	160	<b>\$356.80</b>
1"	<b>L17-800APX</b>	275	<b>388.00</b>
1-1/4"	<b>L17-A00APX</b>	275	<b>403.65</b>
1-1/2"	<b>L17-B00APX</b>	275	<b>403.65</b>

- 1 qt. metal reservoir with drain and oil level sight gauge
- Inlet pressure **250 PSI** maximum
- Particle removal per ISO 8573-1, Class 5 and Class 2
- One turn threaded bowl attachment permits easy maintenance



SCFM ratings at 100 PSI inlet pressure.