



Series 1 Oil-Fog Lubricators

- Oil-fog lubricators, identified by a green adjusting screw, are used for lubricating a single air tool or air motor, and are located as near the device as possible.
- All the oil visible dropping through the transparent sight-feed dome goes to the airstream.
- L72C, L73C and L74C oil-fog lubricators can be filled under pressure.



** Optional pyrex sight-feed dome.
† Minimum clearance required to remove bowl.



** Optional pyrex sight-feed dome.
† Minimum clearance required to remove bowl.

1/2" Basic Transparent Bowl with Guard

Size	Part #	SCFM	Price/E
3/8"	L74C-3	118	\$140.85
1/2"	L74C-4	192	140.85
3/4"	L74C-6	186	140.85




1/2" Basic Metal Bowl with Sight Glass

Size	Part #	SCFM	Price/E
3/8"	L74C-3MB	118	\$144.60
1/2"	L74C-4MB	192	144.60
3/4"	L74C-6MB	186	144.60



- 7 oz. reservoir
- *In-line or modular installation*
- Quick release bayonet bowl
- Inlet pressure for transparent bowl is **150 PSI**
- Inlet pressure for metal bowl is **250 PSI**
- Maximum temperature for transparent bowl is **125°**
- Maximum temperature for metal bowl is **175°F**
- Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at **100°F**

1" Basic Metal Bowl with Sight Glass




1 quart US (1 liter) reservoir
1/4 turn drain

Size	Part #	SCFM	Price/E
3/4"	L17-600D	160	\$283.25
1"	L17-800D	275	283.25
1-1/4"	L17-A00D	275	331.40
1-1/2"	L17-B00D	275	331.40



- 1 qt. metal reservoir with drain and oil level sight gauge
- One turn threaded bowl attachment permits easy maintenance
- Inlet pressure **250 PSI** maximum

General Purpose 2" Ports



Size	Part #	SCFM	Price/E
2"	10-076-004	1000	\$4377.80

- 2 gallon reservoir
- The oil flow can be positively set
- Reservoirs are ASME construction
- Inlet pressure **250 PSI** maximum



SCFM ratings at 100 PSI inlet pressure