

## Watts Filters

### Compact

#### Polycarbonate Bowl with Plastic Bowl Guard




D  
Air  
Fittings

Automatic Drain				Manual Drain			
Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E
1/4"	<b>F602 - 02BJR</b>	55	<b>\$161.85</b>	1/4"	<b>F602 - 02BJ</b>	55	<b>\$105.95</b>
3/8"	<b>F602 - 03BJR</b>	75	<b>161.85</b>	3/8"	<b>F602 - 03BJ</b>	75	<b>105.95</b>

- 5 oz. bowl
- 40 micron polypropylene element
- Zinc body

- Operating conditions:  
Temperature range:  
**40°F (4.4°C) to 120°F (48.9°C)**  
Pressure range:  
**150 PSIG (10.2 bar) maximum**



### Standard


#### Polycarbonate Bowl with Plastic Bowl Guard



Automatic Drain				Manual Drain			
Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E
1/2"	<b>F602 - 04BJR</b>	110	<b>\$201.60</b>	1/2"	<b>F602 - 04BJ</b>	110	<b>\$145.75</b>

- 8 oz. bowl
- 40 micron polypropylene element
- Zinc body

- Operating conditions:  
Temperature range:  
**40°F (4.4°C) to 120°F (48.9°C)**  
Pressure range:  
**150 PSIG (10.2 bar) maximum**



### Standard

#### Zinc Bowl with Sight Glass




- 16 oz. bowl
- 40 micron polypropylene element
- Zinc body

Automatic Drain				Manual Drain			
Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E
3/4"	<b>F602 - 06WJR</b>	250	<b>\$348.05</b>	3/4"	<b>F602 - 06WJ</b>	250	<b>\$292.15</b>
1"	<b>F602 - 08WJR</b>	340	<b>348.05</b>	1"	<b>F602 - 08WJ</b>	340	<b>292.15</b>

- Operating conditions:  
Temperature range:  
**40°F (4.4°C) to 120°F (48.9°C)**  
Pressure range:  
**175 PSIG (12 bar) maximum**

- Operating conditions:  
Temperature range:  
**40°F (4.4°C) to 150°F (65.6°C)**  
Pressure range:  
**250 PSIG (17 bar) maximum**



SCFM ratings at 150 PSIG inlet pressure