



## Filters, Regulators and Lubricators

### Watts Regulators

- Economy of size and high performance
- T-Handle design



#### Compact



With Gauge				Without Gauge			
Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E
1/4"	<b>R11 - 02CG</b>	60	<b>\$109.70</b>	1/4"	<b>R11 - 02C</b>	60	<b>\$87.40</b>
3/8"	<b>R11 - 03CG</b>	70	<b>109.70</b>	3/8"	<b>R11 - 03C</b>	70	<b>87.40</b>
1/2"	<b>R11 - 04CG</b>	80	<b>109.70</b>	1/2"	<b>R11 - 04C</b>	80	<b>87.40</b>

- Reduced pressure range:  
**2 - 125 PSIG (.15 - 8.5 bar)**
- Supply pressure:  
**300 PSIG maximum (20.4 bar)**
- Temperature range:  
**40°F (4.4°C) to 120°F (48.9°C)**

- Diaphragm operated
- Relieving
- Zinc body
- Spring adjustment mechanism
- Standard gauge is GC230



**D**  
Air Fittings



#### Standard



With Gauge				Without Gauge			
Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E
1/4"	<b>R119 - 02CG</b>	60	<b>\$134.10</b>	1/4"	<b>R119 - 02C</b>	60	<b>\$111.75</b>
3/8"	<b>R119 - 03CG</b>	80	<b>134.10</b>	3/8"	<b>R119 - 03C</b>	80	<b>111.75</b>
1/2"	<b>R119 - 04CG</b>	100	<b>153.80</b>	1/2"	<b>R119 - 04C</b>	100	<b>131.45</b>

- Reduced pressure range:  
**2 - 125 PSIG (.15 - 8.5 bar)**
- Supply pressure:  
**300 PSIG maximum (20.4 bar)**
- Temperature range:  
**40°F (4.4°C) to 120°F (48.9°C)**

- Brass bottom plug
- Diaphragm operated
- Zinc body
- Relieving
- Aluminum spring cage
- Spring adjustment mechanism
- Standard gauge is GC230



#### Standard



With Gauge				Without Gauge			
Size	Part #	SCFM	Price/E	Size	Part #	SCFM	Price/E
3/4"	<b>R119 - 06CG</b>	200	<b>\$243.65</b>	3/4"	<b>R119 - 06C</b>	200	<b>\$221.30</b>
1"	<b>R119 - 08CG</b>	220	<b>243.65</b>	1"	<b>R119 - 08C</b>	220	<b>221.30</b>
1-1/2"	<b>R119 - 12CG</b>	250	<b>305.30</b>	1-1/2"	<b>R119 - 12C</b>	250	<b>283.00</b>

- Reduced pressure range:  
**2 - 125 PSIG (.15 - 8.5 bar)**
- Supply pressure:  
**300 PSIG maximum (20.4 bar)**
- Temperature range:  
**40°F (4.4°C) to 120°F (48.9°C)**

- Acetal bottom plug
- Diaphragm operated
- Zinc body
- Relieving
- Aluminum spring cage
- Spring adjustment mechanism
- Standard gauge is GC230

