

Gauges

Brass Liquid Filled Gauges

Designed for severe service in hydraulic systems and other demanding applications.

- 1.5% accuracy on 2½"; 1% accuracy on 4"
- acrylic window with membrane assembly
- copper alloy bourdon tube
- brass movement with highly polished bearing surfaces
- glycerin filled
- ambient temperature range of 0°F to 140°F

2½" face
¼" lower mount

PSI	Fig. Inter.	Grad. Inter.	Part #	Price/E
0-15	3	.2	GLBR15	\$97.55
0-30	5	.5	GLBR30	97.55
0-60	10	1	GLBR60	97.55
0-100	20	2	GLBR100	97.55
0-160	20	2	GLBR160	97.55
0-200	50	5	GLBR200	97.55
0-300	50	5	GLBR300	97.55
0-400	100	10	GLBR400	97.55
0-600	100	10	GLBR600	97.55
0-1000	300	20	GLBR1000	97.55
0-1500	500	20	GLBR1500	109.20
0-2000	500	50	GLBR2000	109.20
0-3000	1000	50	GLBR3000	109.20
0-5000	1000	100	GLBR5000	109.20

2½" face
¼" center back mount

PSI	Fig. Inter.	Grad. Inter.	Part #	Price/E
0-15	3	.2	GLBRC15	\$112.40
0-30	5	.5	GLBRC30	101.80
0-60	10	1	GLBRC60	101.80
0-100	20	2	GLBRC100	101.80
0-160	20	2	GLBRC160	101.80
0-200	50	5	GLBRC200	101.80
0-300	50	5	GLBRC300	101.80
0-400	100	10	GLBRC400	101.80
0-600	100	10	GLBRC600	101.80
0-1000	300	20	GLBRC1000	101.80
0-1500	500	20	GLBRC1500	112.40
0-2000	500	50	GLBRC2000	112.40
0-3000	1000	50	GLBRC3000	112.40
0-5000	1000	100	GLBRC5000	112.40

2½" has solid cast brass case with polished brass slip-fit ring

4" face
½" lower mount

PSI	Fig. Inter.	Grad. Inter.	Part #	Price/E
0-15	3	.2	GLBR15-4	\$249.10
0-30	5	.5	GLBR30-4	249.10
0-60	10	1	GLBR60-4	249.10
0-100	10	1	GLBR100-4	249.10
0-160	20	2	GLBR160-4	249.10
0-200	20	2	GLBR200-4	249.10
0-300	50	5	GLBR300-4	249.10
0-400	50	5	GLBR400-4	249.10
0-600	100	10	GLBR600-4	249.10
0-1000	100	10	GLBR1000-4	249.10
0-1500	300	20	GLBR1500-4	270.30
0-2000	200	20	GLBR2000-4	270.30
0-3000	500	50	GLBR3000-4	270.30
0-5000	500	50	GLBR5000-4	270.30
0-10000	1000	100	GLBR10000-4	381.60

4" has cast brass, silver painted case with chrome plated brass ring



GLBR160

D
Air
Fittings