

Gauges

Liquid Filled Stainless Case Gauges

- helical wound bronze bourdon tube (**1000 PSI** and above)
- white aluminum dial with black numbers and black aluminum pointer
- PowerFlex™ movement with polyester segment designed to resist the effects of shock, vibration and pulsation.
- ¼" NPT brass connection
- glycerin liquid fill
- polycarbonate window
- ambient temperature range **20°F to 150°F**
- ASME B40.1, Grade B (+/- 3-2-3% accuracy)



GLS430

2½" face
¼" lower mount

PSI	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	1	.5	GLS400	\$39.25
0-30	5	.5	GLS405	39.25
0-60	5	1	GLS410	39.25
0-100	10	2	GLS415	39.25
0-160	20	5	GLS417	39.25
0-200	20	5	GLS420	39.25
0-300	30	5	GLS425	39.25
0-400	50	10	GLS427	39.25
0-600	50	10	GLS430	39.25
0-1000	200	20	GLS435	43.50
0-1500	300	50	GLS440	43.50
0-2000	400	50	GLS445	43.50
0-3000	500	100	GLS450	43.50
0-5000	1000	100	GLS455	43.50

2½" face
¼" center back mount

PSI	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	1	.5	GLSC400	\$47.70
0-30	5	.5	GLSC405	47.70
0-60	5	1	GLSC410	47.70
0-100	10	2	GLSC415	47.70
0-160	20	5	GLSC417	47.70
0-200	20	5	GLSC420	47.70
0-300	30	5	GLSC425	47.70
0-400	50	10	GLSC427	47.70
0-600	50	10	GLSC430	47.70
0-1000	200	20	GLSC435	47.70
0-1500	300	50	GLSC440	54.10
0-2000	400	50	GLSC445	54.10
0-3000	500	100	GLSC450	54.10
0-5000	1000	100	GLSC455	54.10



GLSC420

Liquid Filled ABS Case Gauges

2½" face
¼" lower mount

PSI	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	1	.5	GLP500	\$30.75
0-30	5	.5	GLP505	30.75
0-60	5	1	GLP510	30.75
0-100	10	2	GLP515	30.75
0-160	20	5	GLP517	30.75
0-200	20	5	GLP520	30.75
0-300	30	5	GLP525	30.75
0-400	50	10	GLP527	30.75
0-600	50	10	GLP530	30.75
0-1000	200	20	GLP535	35.00
0-1500	300	50	GLP540	35.00
0-2000	400	50	GLP545	35.00
0-3000	500	100	GLP550	35.00
0-5000	1000	100	GLP555	35.00



GLP550