



Washdown Nozzles, Pressure Gun and Accessories

Temperature Indicating Spray Nozzle

When you uncoil your hose and walk away from the hot and cold water mixer, you can no longer read the dial thermometer on the mixer. With the temperature indicating spray nozzle, you take your thermometer with you. 1/2" female NPT inlet. Black cover.

- Easy to read dial thermometer is located at the rear of the nozzle for accurate and continual monitoring of water temperature.
- The dial thermometer is all stainless steel with a plastic sight window, and the entire gauge assembly is recessed into the rubber cover for complete protection.
- Alerts the operator to shut-down the steam valve upon cold water failure, preventing scalding and steam burn injuries (ensures operator safety).
- Ensures a more accurate discharge water temperature reading.
- Recommended for water temperatures to **200°F**
- Maximum operating pressure: **150 PSI**
- **14 GPM** flow capacity



Part #	Price/E
BWSG-TI	\$418.10

Bronze

F
Brass
Fittings

Stainless Steel Industrial Grade Spray Nozzle

The stainless steel industrial grade spray nozzle is recommended for use on corrosive applications where bronze and aluminum are not suitable.

- Heavy duty 300 series stainless steel body and barrel
- Variable spray pattern adjusts from a soft spray to a solid stream
- Replaceable rubber cover is specially formulated to resist a wide range of oils and chemicals. Rubber cover also protects surrounding equipment.
- 1/2" male NPT x 3/4" hose barb 300 series stainless steel swivel adapter
- Maximum operating pressure: **150 PSI**
- **8 GPM** flow capacity at **100 PSI**
- 1/2" female NPT inlet



Part #	Price/E
300SSSG	\$631.45

300 series Stainless Steel

Brass Industrial Grade Front Lever Spray Nozzle

The brass industrial grade spray nozzle provides effortless one hand operation: by actuating the operating lever the valve is opened/closed and the jet power is regulated from spray to concentrated jet.

- Durable nozzle constructed of a high quality brass and steel combination.
- Maximum operating pressure: **350 PSI**
- Suitable for hot water up to **122°F**
- The adjusting screw on the back of the gun allows you to fix the desired form of jet. The fixing clamp for the operating lever allows permanent service.
- **6.6 GPM** flow capacity at **72 PSI**
- 1/2" female NPT inlet



Part #	Price/E
DWG050	\$182.80

Brass