



## Clamps

### Dixon Worm Gear Clamps

#### Style HS Clamps



combination 5/16" hexagon and screwdriver slotted screw

- SAE 201/301 series stainless band and housing with SAE 1018 case-hardened steel, zinc plated and chromate dip screw.
- Upgraded to four-piece construction

#### Style HSS Clamps



all stainless construction 5/16" hexagon and screwdriver slotted screw

- Marine Grade SAE 301/302 series stainless band and housing with SAE 300 series stainless screw.
- Upgraded to four-piece construction

	Hose O.D. Range		Part #	Price/E	Master *
	From:	To:			
1/2" Band Width	28/64"	50/64"	<b>HS6</b>	<b>\$1.25</b>	200
	32/64"	58/64"	<b>HS8</b>	<b>1.25</b>	200
	36/64"	1-4/64"	<b>HS10</b>	<b>1.25</b>	500
	44/64"	1-16/64"	<b>HS12</b>	<b>1.30</b>	500
	52/64"	1-32/64"	<b>HS16</b>	<b>1.30</b>	500
	52/64"	1-48/64"	<b>HS20</b>	<b>1.30</b>	500
	1-4/64"	2"	<b>HS24</b>	<b>1.30</b>	500
	1-20/64"	2-16/64"	<b>HS28</b>	<b>1.30</b>	500
	1-36/64"	2-32/64"	<b>HS32</b>	<b>1.30</b>	500
	1-52/64"	2-48/64"	<b>HS36</b>	<b>1.35</b>	500
9/16" Band Width	2-4/64"	3"	<b>HS40</b>	<b>1.80</b>	200
	2-20/64"	3-16/64"	<b>HS44</b>	<b>2.05</b>	200
	2-36/64"	3-32/64"	<b>HS48</b>	<b>2.05</b>	200
	2-52/64"	3-48/64"	<b>HS52</b>	<b>2.25</b>	200
	3-4/64"	4"	<b>HS56</b>	<b>2.25</b>	200
	3-20/64"	4-16/64"	<b>HS60</b>	<b>2.35</b>	200
	3-36/64"	4-32/64"	<b>HS64</b>	<b>2.35</b>	200
	1-56/64"	5"	<b>HS72</b>	<b>2.50</b>	100
	2-32/64"	5-32/64"	<b>HS80</b>	<b>2.90</b>	100
	3-8/64"	6"	<b>HS88</b>	<b>2.95</b>	100
	3-40/64"	6-32/64"	<b>HS96</b>	<b>3.00</b>	100
	4-8/64"	7"	<b>HS104</b>	<b>3.05</b>	100
	5-40/64"	8-32/64"	<b>HS128</b>	<b>4.10</b>	100
	7-8/64"	10"	<b>HS152</b>	<b>4.40</b>	100
	9-24/64"	12-16/64"	<b>HS188</b>	<b>4.85</b>	100
	10-8/64"	13"	<b>HS200</b>	<b>5.05</b>	100
	10-56/64"	13-48/64"	<b>HS212</b>	<b>5.45</b>	100
	11-40/64"	14-32/64"	<b>HS224</b>	<b>6.00</b>	100
	12-24/64"	15-16/64"	<b>HS236</b>	<b>6.50</b>	100
	13-8/64"	16"	<b>HS248</b>	<b>6.90</b>	100
17-8/64"	20"	<b>HS312</b>	<b>8.40</b>	100	

	Hose O.D. Range		Part #	Price/E	Master *
	From:	To:			
1/2" Band Width	28/64"	50/64"	<b>HSS6</b>	<b>\$1.60</b>	200
	32/64"	58/64"	<b>HSS8</b>	<b>1.60</b>	200
	36/64"	1-4/64"	<b>HSS10</b>	<b>1.60</b>	500
	44/64"	1-16/64"	<b>HSS12</b>	<b>1.65</b>	500
	52/64"	1-32/64"	<b>HSS16</b>	<b>1.65</b>	500
	52/64"	1-48/64"	<b>HSS20</b>	<b>1.70</b>	500
	1-4/64"	2"	<b>HSS24</b>	<b>1.70</b>	500
	1-20/64"	2-16/64"	<b>HSS28</b>	<b>1.70</b>	500
	1-36/64"	2-32/64"	<b>HSS32</b>	<b>1.70</b>	500
	1-52/64"	2-48/64"	<b>HSS36</b>	<b>1.80</b>	500
9/16" Band Width	2-4/64"	3"	<b>HSS40</b>	<b>2.00</b>	200
	2-20/64"	3-16/64"	<b>HSS44</b>	<b>2.30</b>	200
	2-36/64"	3-32/64"	<b>HSS48</b>	<b>2.30</b>	200
	2-52/64"	3-48/64"	<b>HSS52</b>	<b>2.45</b>	200
	3-4/64"	4"	<b>HSS56</b>	<b>2.45</b>	200
	3-20/64"	4-16/64"	<b>HSS60</b>	<b>2.55</b>	200
	3-36/64"	4-32/64"	<b>HSS64</b>	<b>2.55</b>	200
	1-56/64"	5"	<b>HSS72</b>	<b>2.80</b>	100
	2-32/64"	5-32/64"	<b>HSS80</b>	<b>2.90</b>	100
	3-8/64"	6"	<b>HSS88</b>	<b>3.25</b>	100
	3-40/64"	6-32/64"	<b>HSS96</b>	<b>3.35</b>	100
	4-8/64"	7"	<b>HSS104</b>	<b>3.15</b>	100
	5-40/64"	8-32/64"	<b>HSS128</b>	<b>5.00</b>	100
	7-8/64"	10"	<b>HSS152</b>	<b>5.50</b>	100
	9-24/64"	12-16/64"	<b>HSS188</b>	<b>6.00</b>	100
	10-8/64"	13"	<b>HSS200</b>	<b>6.10</b>	100
	10-56/64"	13-48/64"	<b>HSS212</b>	<b>6.40</b>	100
	11-40/64"	14-32/64"	<b>HSS224</b>	<b>6.85</b>	100
	12-24/64"	15-16/64"	<b>HSS236</b>	<b>7.55</b>	100
	13-8/64"	16"	<b>HSS248</b>	<b>8.40</b>	100
17-8/64"	20"	<b>HSS312</b>	<b>9.65</b>	100	

This clamp meets SAEJ1508 which supercedes Mil Spec WW-C-440B.

Maximum recommended torque 50 in. lbs.

Torque ratings given on this page correspond to the torque rating of the screw of the clamp and are not an indication of the working pressure of any hose assembly installed with this clamp.

\* All clamps sold 10 per box