



Clamps

Aero-Seal® Clamps

4-Piece Construction

Band, saddle, housing, screw

Full 9/16" Wide Bands

300-series stainless steel with a finished edge to protect hose

Arcial Band Slots

Arched on one side for strength, flat on bearing side for strength and smooth action.

Buttress-Thread, Heat Treated Screws

Flat, non-tapered threads bear at right angles to band slots on loaded side; won't jump out. Sloping buttress shape reinforces unloaded side.

Clinched Saddle and Housing

No spot welds to corrode or break. Saddle interlocks into embossed band to form a true concentric circle. There are no lumps, no humps, no excessive pressure points, providing higher sealing pressure with lower torque on screw. Heavy-gauge housing is clinched on four corners to interlocked saddle, permitting higher torque capabilities than any 3-piece clamp. Available with safety collar or thumb screw.



Hose O.D. Range	Plated Carbon Steel Screw		No. 410 Stainless Steel Screw		Stainless Steel High Corrosion Resistance		
	From:	To:	Part #	Price/E	Part #	Price/E	Part #
28/64"	50/64"	10006	\$1.75	20006	\$2.20	30006	\$2.50
32/64"	58/64"	10008	1.75	20008	2.20	30008	2.50
36/64"	1-4/64"	10010	1.75	20010	2.20	30010	2.50
44/64"	1-16/64"	10012	1.80	20012	2.25	30012	2.60
52/64"	1-32/64"	10016	1.80	20016	2.25	30016	2.60
52/64"	1-48/64"	10020	1.85	20020	2.30	30020	2.60
1-4/64"	2"	10024	1.85	20024	2.30	30024	2.60
1-20/64"	2-16/64"	10028	1.90	20028	2.35	30028	2.70
1-36/64"	2-32/64"	10032	1.90	20032	2.35	30032	2.70
1-52/64"	2-48/64"	10036	1.95	20036	2.40	30036	2.70
2-4/64"	3"	10040	2.40	20040	2.95	30040	3.30
2-20/64"	3-16/64"	10044	2.60	20044	3.20	30044	3.60
2-36/64"	3-32/64"	10048	2.60	20048	3.20	30048	3.60
2-52/64"	3-48/64"	10052	2.75	20052	3.40	30052	3.85
3-4/64"	4"	10056	2.75	20056	3.40	30056	3.85
3-20/64"	4-16/64"	10060	2.95	20060	3.70	30060	4.10

Maximum recommended torque 50 in/lbs.

Sold 10 per box



HTM Hi Torque Clamps

- Withstands more than three times the SAE torque requirements for worm-driven clamps
- 5/8" wide 300 series half hard stainless steel band
- Eight screw threads are engaged in the band simultaneously for incredible torquing drive (**over 150 in. lbs.**), sealing pressure and vibration resistance
- 410 stainless steel screw



Extended Range Clamps

Hose O.D. Range		Part #	Price/E	Pkg Qty	Hose O.D. Range		Part #	Price/E
From:	To:				From:	To:		
1-16/64"	2-8/64"	HTM200	\$4.55	10	1-16/64"	2-40/64"	HP2	\$4.60
1-48/64"	2-40/64"	HTM250	4.60	10	2-8/64"	4-8/64"	HP3	5.00
2-16/64"	3-8/64"	HTM300	4.75	10	4"	6-8/64"	HP4	5.80
2-48/64"	3-40/64"	HTM350	4.85	10	6-8/64"	9-8/64"	HP5	7.00
3-16/64"	4-8/64"	HTM400	5.00	10				
3-48/64"	4-40/64"	HTM450	5.15	10				
4-16/64"	5-8/64"	HTM500	5.30	10				
4-48/64"	5-40/64"	HTM550	5.65	10				
5-16/64"	6-8/64"	HTM600	5.80	10				
5-48/64"	6-40/64"	HTM650	5.90	10				
6-16/64"	7-8/64"	HTM700	6.10	10				
6-48/64"	7-40/64"	HTM750	6.60	10				
7-16/64"	8-8/64"	HTM800	6.75	10				
7-48/64"	8-40/64"	HTM850	6.85	10				
8-16/64"	9-8/64"	HTM900	7.05	10				

Optional Pkg./Box Quantity Shown