



## Clamps

### Heavy Duty T-Bolt Clamps



**Style HTBC**

stainless steel band, carbon steel bolt

Hose O.D. Range		Part #	Price / Each
From:	To:		
2.125"	2.4375"	<b>HTBC238</b>	<b>\$12.50</b>
2.250"	2.5625"	<b>HTBC250</b>	<b>12.55</b>
2.750"	3.0625"	<b>HTBC300</b>	<b>12.75</b>
3.250"	3.5625"	<b>HTBC350</b>	<b>12.95</b>
3.750"	4.0625"	<b>HTBC400</b>	<b>13.15</b>
4.250"	4.5625"	<b>HTBC450</b>	<b>13.40</b>
4.750"	5.0625"	<b>HTBC500</b>	<b>13.55</b>
5.250"	5.5625"	<b>HTBC550</b>	<b>13.80</b>
5.750"	6.0625"	<b>HTBC600</b>	<b>14.00</b>
6.250"	6.5625"	<b>HTBC650</b>	<b>14.25</b>
6.750"	7.0625"	<b>HTBC700</b>	<b>14.40</b>
7.250"	7.5625"	<b>HTBC750</b>	<b>14.60</b>
7.750"	8.0625"	<b>HTBC800</b>	<b>14.85</b>

- T-bolts can be applied with a standard 1/2" socket wrench.
- 7/8" wide 300 series stainless steel band, .040" thick
- Carbon steel bolt. **Torque rating is 240 in/lbs**

**Style HSTBC**

stainless steel band, stainless steel bolt

Hose O.D. Range		Part #	Price / Each
From:	To:		
2.125"	2.4375"	<b>HSTBC238</b>	<b>\$14.10</b>
2.250"	2.5625"	<b>HSTBC250</b>	<b>14.15</b>
2.750"	3.0625"	<b>HSTBC300</b>	<b>14.40</b>
3.250"	3.5625"	<b>HSTBC350</b>	<b>14.60</b>
3.750"	4.0625"	<b>HSTBC400</b>	<b>14.85</b>
4.250"	4.5625"	<b>HSTBC450</b>	<b>15.05</b>
4.750"	5.0625"	<b>HSTBC500</b>	<b>15.30</b>
5.250"	5.5625"	<b>HSTBC550</b>	<b>15.55</b>
5.750"	6.0625"	<b>HSTBC600</b>	<b>15.75</b>
6.250"	6.5625"	<b>HSTBC650</b>	<b>15.95</b>
6.750"	7.0625"	<b>HSTBC700</b>	<b>16.20</b>
7.250"	7.5625"	<b>HSTBC750</b>	<b>16.40</b>
7.750"	8.0625"	<b>HSTBC800</b>	<b>16.65</b>
8.266"	8.562"	<b>HSTBC850</b>	<b>20.95</b>
8.646"	8.942"	<b>HSTBC888</b>	<b>21.30</b>
8.766"	9.062"	<b>HSTBC900</b>	<b>21.55</b>
9.266"	9.562"	<b>HSTBC950</b>	<b>22.15</b>
9.766"	10.062"	<b>HSTBC1000</b>	<b>22.70</b>
10.646"	10.942"	<b>HSTBC1088</b>	<b>23.90</b>
11.766"	12.062"	<b>HSTBC1200</b>	<b>25.05</b>
12.646"	12.942"	<b>HSTBC1288</b>	<b>26.20</b>

- T-bolts can be applied with a standard 1/2" socket wrench.
- 7/8" wide 300 series stainless steel band, .040" thick
- 300 series stainless steel bolt. **Torque rating is 180 in/lbs**



### Long Bolt T-Bolt Clamps



**Style STBCL**

stainless steel band, stainless steel bolt

Hose O.D. Range		Part #	Price/E	Pkg Qty
From:	To:			
2.80"	3.37"	<b>STBC325L</b>	<b>\$9.40</b>	25
3.05"	3.62"	<b>STBC350L</b>	<b>9.40</b>	25
3.37"	3.94"	<b>STBC382L</b>	<b>9.40</b>	25
3.55"	4.12"	<b>STBC400L</b>	<b>9.45</b>	25
3.75"	4.32"	<b>STBC420L</b>	<b>9.45</b>	25
3.87"	4.44"	<b>STBC432L</b>	<b>9.45</b>	25
4.05"	4.62"	<b>STBC450L</b>	<b>9.45</b>	25
4.37"	4.94"	<b>STBC482L</b>	<b>9.70</b>	25
4.55"	5.12"	<b>STBC500L</b>	<b>9.70</b>	25
4.87"	5.44"	<b>STBC532L</b>	<b>9.70</b>	25
5.05"	5.62"	<b>STBC550L</b>	<b>9.80</b>	25
5.37"	5.94"	<b>STBC582L</b>	<b>9.80</b>	25
5.55"	6.12"	<b>STBC600L</b>	<b>9.85</b>	25
5.87"	6.44"	<b>STBC632L</b>	<b>9.85</b>	25
6.05"	6.62"	<b>STBC650L</b>	<b>9.90</b>	25
6.30"	6.87"	<b>STBC675L</b>	<b>9.90</b>	25

- T-bolts can be applied with a standard 7/16" socket wrench.
- 3/4" wide 300 series stainless steel band, .025" thick
- 300 series stainless steel bolt. **Torque rating is 50 in/lbs**

**Style STBCL**

stainless steel band, stainless steel bolt

Hose O.D. Range		Part #	Price/E	Pkg Qty
From:	To:			
6.53"	7.10"	<b>STBC698L</b>	<b>\$10.10</b>	25
6.55"	7.12"	<b>STBC700L</b>	<b>10.15</b>	25
6.62"	7.19"	<b>STBC707L</b>	<b>10.15</b>	25
8.05"	8.62"	<b>STBC850L</b>	<b>10.15</b>	25
8.30"	8.87"	<b>STBC875L</b>	<b>10.35</b>	25
8.62"	9.19"	<b>STBC907L</b>	<b>10.80</b>	25
10.25"	10.82"	<b>STBC1070L</b>	<b>10.95</b>	25
10.43"	11.00"	<b>STBC1088L</b>	<b>10.95</b>	25
10.62"	11.19"	<b>STBC1107L</b>	<b>11.10</b>	25
10.72"	11.29"	<b>STBC1117L</b>	<b>11.10</b>	25
12.20"	12.77"	<b>STBC1265L</b>	<b>11.55</b>	25
12.43"	13.00"	<b>STBC1288L</b>	<b>11.55</b>	25
12.75"	13.32"	<b>STBC1320L</b>	<b>11.30</b>	25
14.20"	14.77"	<b>STBC1465L</b>	<b>11.35</b>	25
14.43"	15.00"	<b>STBC1488L</b>	<b>11.35</b>	25
14.75"	15.32"	<b>STBC1520L</b>	<b>11.60</b>	25
16.20"	16.77"	<b>STBC1665L</b>	<b>12.00</b>	25
16.43"	17.00"	<b>STBC1688L</b>	<b>12.00</b>	25