



Fire Hose Fittings

All Synthetic Double Jacket Mill Hose - Uncoupled

Ideal for open end discharge applications. *Not intended for fire fighting service.*

Outer construction:

Double jacket, all synthetic

Tube construction:

Black extruded synthetic rubber

Rated pressure: **250 PSI**

Working pressure: **200 PSI**



uncoupled

Uncoupled

Size	Bowl	Length	Part #	Price / Each
1½"	1-13/16"	50'	DM15-50UC	\$258.90
1½"	1-13/16"	100'	DM15-100UC	517.80
2"	2-5/16"	50'	DM20-50UC	302.05
2"	2-5/16"	100'	DM20-100UC	604.10
2½"	2-7/8"	50'	DM25-50UC	361.50
2½"	2-7/8"	100'	DM25-100UC	723.00

* Double jacket hoses are *not* recommended for use with field reattachable couplings (*Flat Seal*).

Double Jacket All Polyester Mill Hose - Coupled

Not intended for fire fighting service.

Outer construction:

Double jacket, all synthetic

Tube construction:

Black extruded synthetic rubber

Rated pressure: **250 PSI**

Working pressure: **200 PSI**



coupled

Coupled with female and male NST (NH) thread, rocker lug, aluminum expansion ring couplings

Size	Bowl	Length	Part #	Price / Each
1½"	1-13/16"	50'	DM15-50RAF	\$236.15
1½"	1-13/16"	100'	DM15100RAF	360.65
2½"	2-7/8"	50'	DM25-50RAF	311.10
2½"	2-7/8"	100'	DM25100RAF	507.85

