

Fire Hose Fittings

## 400# Nitrile Covered Fire Hose - Light Duty - Red

**Outer construction:**

Thin ribbed nitrile

**Tube construction:**

Nitrile

Proof pressure: **400 PSI**

Service test pressure: **200 PSI**

Working pressure: **180 PSI**

- Synthetic rubber compound specially formulated for flexibility, as well as abrasion and chemical resistance. Ribbed for hose protection and easy handling.
- Ideal for industrial and construction washdown and discharge applications.

*Consult the factory for pricing and availability for any of the following features:*

- Hoses coupled with field reattachable couplings (*Flat Seal*).



uncoupled

**Uncoupled**

| Size | Bowl    | Length | Part #           | Price / Each    |
|------|---------|--------|------------------|-----------------|
| 2"   | 2-3/16" | 50'    | <b>H420R50UC</b> | <b>\$472.75</b> |

**Coupled with Female and Male NPSH thread, brass expansion ring couplings with rocker lugs**

| Size | Length | Part #            | Price / Each    |
|------|--------|-------------------|-----------------|
| 2"   | 50'    | <b>H420R50RBS</b> | <b>\$602.70</b> |



coupled

## 500# Nitrile Covered Fire Hose - Light Duty - Red

**Outer construction:**

Thin ribbed nitrile

**Tube construction:**

Nitrile

Proof pressure: **500 PSI**

Service test pressure: **250 PSI**

Working pressure: **225 PSI**

*Consult the factory for pricing and availability for any of the following features:*

- 25' lengths
- Other colors, threads and configurations
- Hoses coupled with field reattachable couplings (*Flat Seal*).
- Ideal for industrial and construction washdown and discharge applications.



uncoupled

**Uncoupled**

| Size | Bowl     | Length | Part #           | Price / Each    |
|------|----------|--------|------------------|-----------------|
| 1½"  | 1-13/16" | 50'    | <b>H515R50UC</b> | <b>\$359.85</b> |
| 2½"  | 2-13/16" | 50'    | <b>H525R50UC</b> | <b>483.70</b>   |

**Coupled with female and male expansion ring couplings**

| Size | Length | Part #         | Rocker Lug Aluminum<br>NST (NH)<br>RAF | Rocker Lug Brass<br>NST (NH)<br>RBF | Pin Lug Brass<br>NST (NH)<br>PBF | Rocker Lug Aluminum<br>NPSH<br>RAS |
|------|--------|----------------|--|-------------------------------------|----------------------------------|------------------------------------|
| 1½"  | 50'    | <b>H515R50</b> | <b>\$424.70</b>                        | <b>\$451.15</b>                     | <b>\$451.15</b>                  | <b>\$424.70</b>                    |
| 2½"  | 50'    | <b>H525R50</b> | <b>589.85</b>                          | <b>655.05</b>                       | <b>655.05</b>                    | <b>589.85</b>                      |



coupled

Fire Hose Fittings