



Fire Hose Fittings

Roof Connections

Used to create roof connections, fire pump test connections, wall hydrants or sidewalk (free standing) hydrants.

- Cast brass
- For pressures up to **175 PSI**
- Provides 250 GPM minimum per outlet

Shape	Female NPT Inlet	(2) Male Outlets	Dixon Part #	Powhatan Part #	Price / Each
straight	4"	2½" NPT	FRC4025 ¹	26-294-00001	\$250.00
straight	4"	2½" NST	FRC4025F ¹	26-294-00003	250.00
straight	6"	2½" NPT	FRC6025 ¹	26-294-00010	455.80
straight	6"	2½" NST	FRC6025F	26-294-00011	455.80
90°	4"	2½" NPT	90FRC4025	26-296-00002	322.25
90°	4"	2½" NST	90FRC4025F	26-296-00003	322.25
90°	6"	2½" NPT	90FRC6025 ¹	26-296-00008	530.75
90°	6"	2½" NST	90FRC6025F	26-296-00011	530.75



¹ Underwriters Listed

Roof manifolds are also available, consult the factory for pricing and availability.

Single Clapper Siamese



Single swing clapper with (2) pin lug swivel inlets. Provides the required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply. (250 GPM minimum per inlet.) The swing clapper design provides an unobstructed waterway. Exposed Fire Department Connections (FDC) provide an economical method to satisfy local fire codes.

- Underwriters Listed and Factory Mutual approved
- Cast brass finish
- Branding: Auto-Spkr only
- For use up to **250 PSI**

Shape	Female Outlet NPT	(2) Female Inlets NH (NST)	Dixon Part #	Powhatan Part #	Price / Each
Straight	4"	2½"	SCS4025F	21-201-01976	\$255.50
90°	4"	2½"	90SCS4025F	21-202-00054	296.60



Double Clapper Siamese



Double drop clappers with (2) pin lug swivel inlets. Provides the required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply (250 GPM minimum per inlet.) Exposed Fire Department Connections (FDC) provide an economical method to satisfy local fire codes.

- Cast brass finish
- Branding: Auto-Spkr ²
- For use up to **175 PSI**

Shape	Female Outlet NPT	(2) Female Inlets NH (NST)	Dixon Part #	Powhatan Part #	Price / Each
straight	4"	2½"	DCS4025F ¹	21-132-00016	\$425.00
90°	4"	2½"	90DCS4025F ¹	21-133-00008	473.05
straight	6"	2½"	DCS6025F	21-132-00061	781.10
90°	6"	2½"	90DCS6025F	21-133-00060	668.75



¹ Underwriters Listed and Factory Mutual approved

² Other branding also available

Fire Hose Fittings