

Aluminum Ball Shut-Off Nozzle - Bolted Style

- Lightweight cast aluminum body with pistol grip
- Hardcoated female swivel inlet and male outlet
- Maximum operating pressure to **200 PSI (water only)**

Inlet Thread	Outlet Thread	Waterway	Part #	Price / E
1½" Female NST (NH)	1½" Male NST (NH)	1-3/8"	ACPSO150F	\$485.85



Brass Shut-Off Nozzles

- For use up to **100 PSI (water only)**
- Straight stream only
- Polished brass finish

Base Thread	Tip Thread	GPM @ 100 PSI *	Orifice	Length with Tip	Dixon Part #	Powhatan Part #	Price/E
1½" NPSH	1" NST (NH)	74	½"	9"	BSN150	01-111-50001	\$955.75
1½" NST	1" NST (NH)	74	½"	9"	BSN150NST	01-111-50000	955.75
Replacement handle					BSN150-H	43-111-00004	112.50



* Flow rate with standard ½" orifice tip

Ball Shut-Off Nozzles

- Full time swivel base ensures the durable rubber-like handle is positioned for easy operation
- For use up to **100 PSI (water only)**

Base Thread	Tip Thread	Waterway	Length	Brass Part #	Price / E
1½" NST (NH)	1½" NST (NH)	1-3/8"	4¾"	BSO150NST	\$991.00
Replacement Handle				BSO150-H	64.30



Nozzle Tips

- For use up to **100 PSI (water only)**

Size	Thread	GPM @ 100 PSI	Orifice	Length	Tip Part #	Powhatan Part #	Price / E
1"	NST (NH)	74	½"	4-3/4"	BNT100F	01-128-00036	\$123.25
1½"	NST (NH)	74	½"	4-3/8"	BNT150F	01-128-00094	209.50



Fire Hose Fittings