



Fire Hose Fittings

Forestry Fog Nozzles



FFN75GHT



FFN100



FFN150NST

- 6061-T6 aluminum, corrosion resistant plated
- Maroon hardcoated barrel allows for easy identification
- Offers two straight stream and two fog patterns
- Combination fog and straight stream
- Dual flow rate nozzles
- Operating pressure up to **600 PSI (water only)**

Size	Thread	Dual Flow Rates		NSN	Forestry Service Specification	Part #	Price / Each
		1st Straight Stream GPM @ 100 PSI	2nd Straight Stream GPM @ 100 PSI				
¾"	GHT	1-2 *	3-4 *	---	---	FFN75GHT	\$98.45
1"	NPSH	12	25	4210-01-165-6603	5100-239A	FFN100	164.10
1½"	NPSH	25	70	---	5100-107A	FFN150	269.60
1"	NST (NH)	12	25	---	5100-239A	FFN100NST	164.10
1½"	NST (NH)	25	70	4210-01-167-1123	5100-107A	FFN150NST	269.60

* GPM rating @ 40 PSI



Straight Stream Forestry Nozzles

- Base nozzle has a ½" orifice
- One-piece reversible twin tips have ¼" and 3/8" orifices.
- Overall length with tip: 9"
Overall length without tip: 7-1/8"
- For use up to **100 PSI (water only)**

Size	Part #	Price / Each
1½" NPSH	PTTF150S	\$27.15
1½" NST (NH)	PTTF150F	27.15

Ball Shut-Off Nozzles - Forestry Grade



- Cast aluminum, anodized body, hardcoated threads, and acetal ball
- 1" - 1½" working pressure up to **600 PSI**; 2½" working pressure up to **400 PSI**

Size	Thread	Waterway	Part #	Price / Each
1"	NPSH	¾"	FBSO100S	\$254.00
1½"	NPSH	1"	FBSO150S	271.00
1"	NST (NH)	¾"	FBSO100F	254.00
1½"	NST (NH)	1"	FBSO150F	271.00
2½"	NST (NH)	2½"	FBSO250F	594.00

Aluminum ¼ Turn Ball Type Wye Valves - Forestry Grade

- Cast aluminum, anodized body, hard-coated threads
- Swivel inlet
- Water/AFFF
- Built to United States Forest Service specifications



Female x Male	PSI	Part #	Price / E
1" NPSH x 1" NPSH	600	FWV10S10S	\$419.65
1½" NST (NH) x 1" NPSH	600	FWV15F10S	509.60
1½" NST (NH) x 1½" NST (NH)	600	FWV15F15F	479.60
2½" NST (NH) x 1½" NST (NH)	400	FWV25F15F	544.75
2½" NST (NH) x 2½" NST (NH)	400	FWV25F25F	1122.30