Mini Ball Valves

- Rated to 150 PSI
- Nickel plated brass body
- Teflon® seats and Buna-N stem seal
- Blow-out proof stem
- Temperature range to 150°F
- American Gas Association and Canadian Gas Association approved



Size	Port	Part #	Price / E
1/8" 1/4" 3/8"	standard full full	MBV12 MBV25 MBV38	\$13.75 13.75 12.80
1/2"	standard	MBV50	18.80




Female NPT x Female NPT

Safety Vented Ball Valves

- · For air service only
- 150 PSI saturated steam
- Lockable ball valves vent downstream air in accordance with new OSHA regulations for pneumatic systems.
- Brass valve
- Chromium plated ball
- RTFE seats and stuffing box ring
- Blow-out proof stem design
- Adjustable packing gland

Size	Port	Part #	Price / E
1/4"	full	BBV25LV	\$37.55
3/8"	full	BBV38LV	37.55
1/2"	full	BBV50LV	37.55
3/4"	standard	BBV75LV	54.20
1"	standard	BBV100LV	69.25
1-1/4"	standard	BBV125LV	109.45
1-1/2"	standard	BBV150LV	134.15
2"	standard	BBV200LV	162.80



Female NPT x Female NPT

Bronze "Deadman" Spring Return Handle Ball Valves

- Rated to 600 PSI WOG; 150 PSI saturated steam
- Vacuum service to 29 inches Hg
- Threaded bronze valve
- Stainless steel lever
- Chromium plated ball
- RTFE seats and stuffing box ring
- Blow-out proof stem design
- Adjustable packing gland
- Spring return closes valve when not held open
- Operating torque approximately three times standard valve torque.

Size	Port	Part #	Price / E
1/2"	full	BBV50SR	\$187.65
3/4"	standard	BBV75SR	210.30
1"	standard	BBV100SR	224.65
1½"	standard	BBV150SR	345.40
2"	standard	BBV200SR	406.30



Female NPT x Female NPT

M Valves

See page 550 for valve diagrams

DPL108 429





DPL 10