



Valves

Spring-Loaded Check Valves

- 1½" - 2" rated to **400 PSI** WOG;
3" - 4" rated to **175 PSI** WOG
- Cracking pressure: **0.50 PSI**
- Brass with NBR seat

- Soft seat for bubble tight shutoff, spring loaded for fast seating action
- Flow profile designed to minimize head loss
- Temperature range **10°F to 210°F** (-10°C to 100°C)

Size	Part #	Price/Ea	Size	Part #	Price/Ea
½"	CV050 *	\$16.35	1½"	CV150 *	\$69.60
¾"	CV075 *	21.90	2"	CV200 *	99.00
1"	CV100 *	29.60	3"	CV300	312.25
1¼"	CV125 *	46.65	4"	CV400	483.35



* NSF61 approved

Strainer with Spring-Loaded Check Valve

- 1½" - 2" rated to **400 PSI** WOG;
3" - 4" rated to **175 PSI** WOG
- Cracking pressure: **0.50 PSI**
- Brass with NBR seat
- Stainless steel strainer

- Soft seat for bubble tight shutoff, spring loaded for fast seating action.
- Flow profile designed to minimize head loss
- Temperature range **10°F to 210°F** (-10°C to 100°C)

Size	Part #	Price / Each
1½"	BVFS20 *	\$78.65
2"	BVFS25 *	123.75
3"	BVFS35	333.05
4"	BVFS40	502.30



* NSF61 approved

Horizontal Swing Check Valves

- Swing check valves are designed to prevent back flow in plumbing and liquid piping systems, while offering full flow performance with a minimum of turbulence or pressure loss.
- A positive seating disc allows flow only in one direction and a screw-in cap provides easy access for periodic cleaning.

- For horizontal or vertical use
- Rated to **200 PSI** WOG
- Brass body
- Brass disc
- Temperature range **-20° to 150°F**

Size	Part #	Price / Each
½"	SWCV50	\$22.10
¾"	SWCV75	28.95
1"	SWCV100	39.50
1¼"	SWCV125	58.80
1½"	SWCV150	79.00
2"	SWCV200	116.50
3"	SWCV300	344.20




Female NPT x Female NPT

Ball Cone Check Valves

- For use with water, oil, air lines or inert gases. Not recommended for use on or near reciprocating pumps or other similar **vibration causing machinery**.
- Tight shut-off with liquid media
- No radial alignment necessary
- Straight through and streamlined for minimum change in velocity
- Reinforced TFE check is spring loaded for fast seating action.

- Rated to **400 PSIG** WOG, cold non-shock; **125 PSIG** saturated steam
- Cracking pressure is **.5 PSI**
- Temperature range **-20°F to 353°F**



Female NPT x Female NPT

Size	Brass Part #	Price / Each	Stainless Steel Part #	Price / Each
1/4"	61-101	\$43.85	62-101	\$107.00
3/8"	61-102	43.85	62-102	107.00
1/2"	61-103	43.85	62-103	125.75
3/4"	61-104	62.55	62-104	202.00
1"	61-105	84.75	62-105	275.00
1-1/4"	61-106	149.80	---	---
1-1/2"	61-107	190.70	---	---
2"	61-108	310.80	---	---
2-1/2"	61-109	634.05	---	---
3"	61-100	1060.35	---	---

Pressure/Temperature Ratings

Degrees in Farenheit	Pressure WOG
-20 to 100	400
200	200
250	160
275	150
300	140
325	130
353	125

M
Valves