Maintenance and Repair

Joint Sealant Gasket Material

- GORE-TEX[®] Interchangeable
- Form-In-Place expanded PTFE gasket material with adhesive backing
- Manufactured from 100% virgin PTFE
- Unaffected by all common chemicals (ph from 0-14)
- · Unlimited shelf life
- Resilient with low cold flow
- Requires less comprehensive force than standard gasket materials
- Pressure range from vacuum to 3000 PSI
- Temperature range from -450° to 600°F
- Made in the USA
- Larger spools are available, consult factory for price and availability

Size	Part #	Price / Each
1/4" x 20'	LCJS4-20	\$53.05
1/4" x 50'	LCJS4-50	121.25
3/8" x 25'	LCJS6-25	100.80
1/2" x 15'	LCJS8-15	100.80
3/4" x 15'	LCJS12-15	233.35



Leak Detector

- Detects leaks by forming bubbles which remain for up to 10 minutes
- Will not cause corrosion or deterioration
- Color: fluorescent yellow
- Non-toxic, non-freezing
- Temperature range: -7° (-20°C) to 180°F (82°C)
- Meets Federal spec. MIL-L-25567-C

Qty per Case	Part #	List Each	
24	LCLD	\$8.60	



Dixon Coupling Lubricant

For use in assembly operations involving natural or synthetic rubber or plastic. Also an excellent lubricant when rubber or plastic needs to be cut, machined, pressed, turned, trimmed or ground.

Lubricant for coupling shanks

Size	Part #	Price/E
1 pint	DCL10	\$18.15
1 gallon	DCL80	69.40



WD-40

Call Toll Free: 1-866-711-4

WebSales@GoodyearRubberProducts.com

• Should not be used as a lubricant for coupling shanks

11 oz. cans

Qty per Case	Part #	List Each
12	WD40	\$12.55

Sold in case quantities only





501

We Ship

World Wide