

Horizontal Swing Check Valves

- Swing check valves are designed to prevent back flow in plumbing and liquid piping systems, while offering full flow performance with a minimum of turbulence or pressure loss
- A positive seating disc allows flow only in one direction and a screw-in cap provides easy access for periodic cleaning
- For horizontal or vertical use
- Brass body and disc
- Temperature range **-20° to 150°F**
- Rated to **200 PSI** WOG



Male NPT	Dixon Part #
1/2"	SWCV50
3/4"	SWCV75
1"	SWCV100
1 1/4"	SWCV125
1 1/2"	SWCV150
2"	SWCV200
3"	SWCV300

Straight Ball Drip Valves 23-148

This valve is designed to drain the low point of a system. It should be placed between the fire department connection and the swing check valve.

- Will seal automatically under pressure
- Install in the horizontal position only
- Working pressure: **175 PSI**



Male NPT	Male NPT	Dixon Part #	Powhatan Part #
1/2"	1/2"	SBDV50	23-148-00001
3/4"	3/4"	SBDV75	23-148-00002

Angled Ball Drip Valves 23-181



Male NPT	Male NPT	Dixon Part #	Powhatan Part #
1/2"	1/2"	ASBDV50	23-181-00001
3/4"	3/4"	ASBDV75	23-181-00002