



Thermoplastic Fog Nozzle

- Red polycarbonate with brass stem
- Adjusts from Straight Stream to Fog Shutoff - Straight Stream - Fog
- Factory Mutual approved
- For use up to **100 PSI** (water only)



Size	Thread	90° Spray GPM @100PSI	Dixon Part #	Dixon Part # without bumper	Wt. Lbs.
3/4"	GHT	† 30.9	FNB75GHT	---	0.32
3/4"	NPS	† 30.9	FNB75S	---	0.33
1"	NPS	† 30.9	FNB100S *	FN100S	0.49
1 1/2"	NPS	83.6	FNB150S	FN150S	0.58
1"	NH (NST)	30.9	FNB100NST *	FN100NST	0.49
1 1/2"	NH (NST)	83.6	FNB150NST	FN150NST	0.57

† 120° Spray GPM @100 PSI

* Standard flow

** High flow



Thermoplastic All-Fog Nozzles for Use Around Electrical Equipment

- Red polycarbonate with brass stem
- Opens and closes in a 30° fog pattern up to 120°
- Factory Mutual approved
- For use up to **100 PSI** (water only)



Size	Thread	75° Spray GPM @100PSI	Dixon Part #	Wt. Lbs.
1 1/2"	NPS	92	FNBE150S	.57
1 1/2"	NH (NST)	92	FNBE150NST	.56

Gaskets for Thermoplastic Fog Nozzles

- Material: Buna-N

All dimensions are nominal



Size	Thread type	ID	OD	Thickness	Dixon Part #	Wt. Lbs.
1"	NPS	0.937"	1.234"	0.125"	FNG100S	.001
1"	NPS	1.000"	1.375"	0.125"	HGG100S	
1 1/2"	NPS	1.500"	1.827"	0.125"	FNG150S	.01
1"	NH (NST)	0.937"	1.281"	0.125"	FNG100NST	.001
1"	NH (NST)	1.000"	1.375"	0.125"	HGG100NST	
1 1/2"	NH (NST)	1.510"	1.906"	0.125"	FNG150NST	.01