

## Forest Green Constant Flow Nozzle

- Shatterproof and UV resistant GE Lexan® is able to withstand tough environmental conditions
- Seals used for true water shut off
- Easy twist spray pattern adjustment
- Sold in case quantity only, with display
- 25 nozzles per case

Thread Size	45° Spray GPM @ 100 PSI	Dixon Part #
¾" GHT	25.1	<b>FNB75GHT-GD</b>



## Red Polycarbonate Plain Hose Nozzles

- For use up to **100 PSI** (water only)

Size	Thread	Length	Orifice	Dixon Part #	Wt. Lbs.
1½"	NPSH	10"	½"	<b>PN15</b>	0.22
1½"	NH (NST)	10"	½"	<b>PN15F</b>	0.19



## Thermoplastic Penetrator Nozzles

The black and yellow penetrator nozzle is designed with standard 1-1/2" NPSH male hose threads, that are converted to female thread for connection to the hose using a double female rigid connector. It is specifically designed with a 1/4" discharge orifice, which generates a high velocity water jet that is effective against deep seated wildland fires.

- For use up to **200 PSI** (water only)

Size	Thread	Length	Orifice	Dixon Part #
1½"	NH (NST)	5½"	¼"	<b>PFN4005F</b>



## Twin Tip Straight Stream Forestry Nozzles

- Molded high strength red polycarbonate
- The solid one piece reversible twin tips have 1/4" and 3/8" orifices
- For use up to **100 PSI** (water only)

Size	Thread	Length with tip	Length without tip	Orifice of base nozzle	Dixon Part #	Wt. Lbs.
1½"	NPSH	9"	7½"	½"	<b>PTTF150S</b>	0.3
1½"	NH(NST)	9"	7½"	½"	<b>PTTF150F</b>	0.3

