

## Aluminum Single Gallonage Constant Flow Fog Nozzles



Combine the benefits of an automatic nozzle with the simplicity of a single gallonage nozzle to provide one of the most versatile and easy-to-use nozzles in today's fire service. Quality stream performance at a variety of pressures, combined with a durable and simple design makes this an unbeatable value. Live swivel inlet, and spinning teeth.

- For use up to **100 PSI** (water only)

Size	Thread	Constant GPM @100PSI	Dixon Part #	Wt. Lbs.
1"	NH (NST)	40	<a href="#">AK4802F</a> *	3.3
1½"	NH (NST)	125	<a href="#">AK4820F</a> *	4.8
2½"	NH (NST)	200	<a href="#">AK4825F</a>	7.1

\* supplied with pistol grip



## Aluminum Adjustable Constant Gallonage Fog Nozzles



These are live swivel inlet constant gallonage nozzles (flow remains the same in all patterns) with multiple flow settings for the combination of flow and control. Tight, hard hitting straight stream and wide dense fog pattern.

- For use up to **100 PSI** (water or foam only)
- Quality flow performance as low as 50 PSI

Size	Thread	Constant GPM @100PSI	Dixon Part #	Wt. Lbs.
1"	NH (NST)	13-25-40-60	<a href="#">AK1702F</a> *	3.0
1½"	NH (NST)	30-60-95-125	<a href="#">AK1720F</a> *	4.0
2½"	NH (NST)	125-150-200-250	<a href="#">AK1725F</a>	6.3

\* supplied with pistol grip



## Aluminum Ball Shutoff Nozzle - Bolted Style



- Rugged and lightweight
- Cast aluminum body with pistol grip
- Hardcoated female swivel inlet and male outlet
- For use up to **200 PSI** (water only)

Size	Thread	Waterway	Dixon Part #	Wt. Lbs.
1½"	NH (NST)	1-3/8"	<a href="#">ACPSO150F</a>	2.9