

## Ball Shut-Off Forestry Grade Nozzles

- Durable and lightweight
- Cast aluminum, anodized body, hard-coated threads and acetal ball
- Built to US Forest Service specifications
- For use up to **600 PSI** (1" - 1½"), **400 PSI** (2½")

| Size | Thread   | Waterway | Dixon Part #    | Wt. Lbs. |
|------|----------|----------|-----------------|----------|
| 1"   | NPSH     | ¾"       | <b>FBSO100S</b> | 0.92     |
| 1½"  | NPSH     | 1"       | <b>FBSO150S</b> | 1.23     |
| 1"   | NH (NST) | ¾"       | <b>FBSO100F</b> | 5.8      |
| 1½"  | NH (NST) | 1"       | <b>FBSO150F</b> |          |
| 2½"  | NH (NST) | 2½"      | <b>FBSO250F</b> |          |



## Aluminum Forestry Fog Nozzles

- Maroon hard-coated barrel allows for easy identification
- 6061-T6 aluminum, corrosion resistant plated
- Dual flow rate nozzles offer two straight stream and two fog patterns
- Combination fog and straight stream
- For use up to **600 PSI** (water only)

| Size | Thread   | GPM @100 PSI Straight Stream |                  | Dixon Part #                  | Wt. Lbs. |
|------|----------|------------------------------|------------------|-------------------------------|----------|
|      |          | 1st                          | 2nd              |                               |          |
| ¾"   | GHT      | 1-2 <sup>1</sup>             | 3-4 <sup>1</sup> | <b>FFN75GHT</b>               | 0.57     |
| 1"   | NPSH     | 12                           | 25               | <b>FFN100</b> <sup>2</sup>    |          |
| 1½"  | NPSH     | 25                           | 70               | <b>FFN150</b>                 | 1.00     |
| 1"   | NH (NST) | 12                           | 25               | <b>FFN100NST</b>              | 0.87     |
| 1½"  | NH (NST) | 25                           | 70               | <b>FFN150NST</b> <sup>3</sup> |          |



**FFN75GHT**



**FFN100**



**FFN150NST**

<sup>1</sup> GPM @ 40 PSI

<sup>2</sup> **FFN100** meets USFS 5100-239A and NSN 4210-01-165-6603

<sup>3</sup> **FFN150NST** meets USFS 5100-107A and NSN 4210-01-167-1123

## Aluminum Fog Nozzles



- Manufactured from extruded aluminum
- Rugged lightweight corrosion resistant
- Supplied without bumper
- For cabinet use, discourages theft
- Factory Mutual approved
- For use up to **100 PSI** (water only)

| Size | Thread   | 90° Spray GPM @60PSI | Dixon Part #     | Wt. Lbs. |
|------|----------|----------------------|------------------|----------|
| 1½"  | NPS      | 52                   | <b>AFN150</b>    | 0.66     |
| 1½"  | NH (NST) | 52                   | <b>AFN150NST</b> | 0.66     |

