

500# Single Jacket All-Polyester Fire Hose - White

Ideal for open end discharge applications.
Not intended for fire fighting service.

- Outer construction: single jacket, all polyester
- Tube construction: black, extruded synthetic rubber
- Uncoupled
- Proof Pressure: **500 PSI**
- Service Test Pressure: **250 PSI**
- Working Pressure: **225 PSI**



Hose Size	Bowl Size	Length	Dixon Part #
1½"	1-13/16"	50'	A515-50UC
1½"	1-13/16"	100'	A515-100UC
2½"	2-7/8"	50'	A525-50UC
2½"	2-7/8"	100'	A525-100UC

- Coupled with female and male expansion ring couplings

Thread NH (NST)	Coupling Type	Length	Dixon Part #
1"	Rocker lug, <i>aluminum</i>	50'	A510-50RAF
1½"	Rocker lug, <i>aluminum</i>	50'	A515-50RAF
1½"	Rocker lug, <i>aluminum</i>	100'	A515100RAF
1½"	Rocker lug, <i>brass</i>	50'	A515-50RBF
1½"	Rocker lug, <i>brass</i>	100'	A515100RBF
1½"	Pin lug, <i>brass</i>	50'	A515-50PBF
1½"	Pin lug, <i>brass</i>	100'	A515100PBF
2½"	Rocker lug, <i>aluminum</i>	50'	A525-50RAF
2½"	Rocker lug, <i>aluminum</i>	100'	A525100RAF
2½"	Rocker lug, <i>brass</i>	50'	A525-50RBF
2½"	Rocker lug, <i>brass</i>	100'	A525100RBF



- Coupled with female and male expansion ring couplings

Thread NPSH	Coupling Type	Length	Dixon Part #
1½"	Rocker lug, <i>aluminum</i>	50'	A515-50RAS
1½"	Rocker lug, <i>aluminum</i>	100'	A515100RAS
1½"	Rocker lug, <i>brass</i>	50'	A515-50RBS
1½"	Rocker lug, <i>brass</i>	100'	A515100RBS
2½"	Rocker lug, <i>aluminum</i>	50'	A525-50RAS
2½"	Rocker lug, <i>aluminum</i>	100'	A525100RAS

- Other lengths, threads and couplings are also available. *Consult the factory for pricing and availability.*

* Working pressures can be achieved using appropriate expansion ring couplings.
Under no circumstance should the hose be used beyond the working pressure of the fittings to which it is coupled.
 Assembled hose should be hydrostatically proof tested before use, and thereafter in accordance with NFPA 1962.



500# Single Jacket All-Polyester Fire Hose - UL labeled

- Outer construction: single jacket, all polyester
- Tube construction: black, extruded synthetic rubber
- Coupled with female and male expansion ring couplings
- Proof Pressure: **500 PSI**
- Service Test Pressure: **250 PSI**
- Working Pressure: **225 PSI**



Thread NH (NST)	Coupling Type	Length	Dixon Part #
1½"	Rocker lug, <i>brass</i>	50'	A515U50CBF
1½"	Rocker lug, <i>brass</i>	75'	A515U75CBF
1½"	Rocker lug, <i>brass</i>	100'	A515U100CBF

- Impregnated hose, other lengths, threads and couplings are also available.
Consult the factory for pricing and availability.