

500# Single Jacket All-Polyester Fire Hose - Red Impregnated

- Outer construction: single jacket, all polyester
- Tube construction: black, extruded synthetic rubber
- Impregnation: red
- Proof Pressure: **500 PSI**
- Service Test Pressure: **250 PSI**
- Working Pressure: **225 PSI**
- Coupled with female and male expansion ring couplings

Hose Size	Thread NH (NST)	Coupling Type	Length	Dixon Part #
1½"	1½"	Rocker lug, aluminum	50'	A515R50RAF
1¾"	1½"	Rocker lug, aluminum	50'	A517R50RAF
2½"	2½"	Rocker lug, aluminum	50'	A525R50RAF
3"	2½"	Rocker lug, aluminum	50'	A5325R50RAF



- Other lengths, threads and couplings are also available. Consult the factory for pricing and availability.
- Available impregnation colors: yellow, red, blue, tan, orange, green and black

MSHA Approved, 500# Single Jacket Mine Fire Hose

- Outer construction: single jacket, synthetic *flame resistant*
- Tube construction: black, neoprene rubber *flame resistant*
- Proof Pressure: **400 PSI**
- Service Test Pressure: **200 PSI**
- Working Pressure: **180 PSI**
- Coupled with female and male expansion ring couplings

Thread NH (NST)	Coupling Type	Length	Dixon Part #
1½"	Rocker lug, aluminum	50'	SM515W50RAF
1½"	Rocker lug, aluminum	100'	SM515W100RAF
2½"	Rocker lug, aluminum	50'	SM520W50RAF



- Coupled with female and male expansion ring couplings

Thread NPSH	Coupling Type	Length	Dixon Part #
1½"	Rocker lug, aluminum	50'	SM515W50RAS
2½"	Rocker lug, aluminum	50'	SM520W50RAS

- Other lengths, threads and couplings are also available. Consult the factory for pricing and availability.
- Approved by MSHA :
Mine Safety and Health Administration for all mine fire protection applications
(above or below ground)