## 800# Double Jacket All-Polyester Fire Hose - White

- · Outer construction: double jacket, all polyester
- Tube construction: black, extruded synthetic rubber EPDM rubber lining
- Proof Pressure: 800 PSI
- Service Test Pressure: 400 PSI
- Working Pressure: 360 PSI

· Coupled with female and male expansion ring couplings

| Thread<br>NH (NST) | Coupling<br>Type     | Length | Dixon<br>Part # |
|--------------------|----------------------|--------|-----------------|
| 1½"                | Rocker lug, aluminum | 25'    | D815-25RAF      |
| 1½"                | Rocker lug, aluminum | 50'    | D815-50RAF      |
| 1½"                | Rocker lug, aluminum | 100'   | D815-100RAF     |
| 1½"                | Rocker Lug, brass    | 50'    | D815-50RBF      |
| 1½"                | Rocker Lug, brass    | 100'   | D815-100RBF     |
| 2½"                | Rocker lug, aluminum | 25'    | D825-25RAF      |
| 21/2"              | Rocker lug, aluminum | 50'    | D825-50RAF      |
| 2½"                | Rocker lug, aluminum | 100'   | D825-100RAF     |
| 21/2"              | Rocker Lug, brass    | 50'    | D825-50RBF      |
| 2½"                | Rocker Lug, brass    | 100'   | D825-100RBF     |



Coupled with female and male expansion ring couplings

| Thread<br>NPSH | Coupling<br>Type     | Length | Dixon<br>Part # |
|----------------|----------------------|--------|-----------------|
| 1½"            | Rocker lug, aluminum | 50'    | D815-50RAS      |
| 1½"            | Rocker lug, aluminum | 100'   | D815-100RAS     |
| 1½"            | Rocker Lug, brass    | 50'    | D815-50RBS      |
| 11/2"          | Rocker Lug, brass    | 100'   | D815-100RBS     |
| 21/2"          | Rocker lug, aluminum | 50'    | D825-50RAS      |
| 21/2"          | Rocker lug, aluminum | 100'   | D825-100RAS     |
| 2½"            | Rocker Lug, brass    | 50'    | D825-50RBS      |

- Other lengths, threads and couplings are also available.
  Consult the factory for pricing and availability.
- Double jacket hoses are NOT recommended for use with Dixon's flat seal re-attachable couplings.

## 800# Double Jacket All-Polyester Fire Hose Yellow Impregnated

- · Outer construction: double jacket, all polyester
- Tube construction: black, extruded synthetic rubber
- Impregnation color: yellow

- Proof Pressure: 800 PSI
- Service Test Pressure: 400 PSI
- Working Pressure: 360 PSI

· Coupled with female and male expansion ring couplings

| Thread   | Coupling                    | Length | Dixon      |
|----------|-----------------------------|--------|------------|
| NH (NST) | Type                        |        | Part #     |
| 1½"      | Rocker lug, <i>aluminum</i> | 50'    | D815Y50RAF |
| 1½"      | Rocker Lug, <i>brass</i>    | 50'    | D815Y50RBF |
| 1½"      | Rocker lug, <i>aluminum</i> | 50'    | D817Y50RAF |
| 2½"      | Rocker lug, aluminum        | 50'    | D825Y50RAF |
| 2½"      | Rocker Lug, brass           | 50'    | D825Y50RBF |



- Other lengths, threads and couplings are also available.
  Consult the factory for pricing and availability.
- · Available impregnation colors: yellow, red, blue, tan, orange, green, black
- Double jacket hoses are NOT recommended for use with Dixon's flat seal re-attachable couplings.

