

Aluminum Expansion Ring Rocker Lug Couplings



- *Special tooling is required to attach these couplings to hose*
- Hardcoated finish
- All couplings come complete with expansion rings, swivel and tail washers
- 3 rocker lugs on male and female

- *Rack hose*
- Lugs on female *only*
- Working pressure: **225 PSI**

Hose Size	Thread Type	Bowl Size	Dixon Part #
1½"	NPSH	1-11/16"	RH16168
1½"	NH (NST)	1-11/16"	RH16168F

- *Single jacket*
- Lugs on female and males
- Working pressure: **270 PSI**

Hose Size	Thread Type	Bowl Size	Dixon Part #
1½"	NPSH	1-11/16"	S16168
1½"	NPSH	1-3/4"	S16175
1½"	NPSH	1-13/16"	S16181
2½"	NPSH	2-11/16"	S26268
2½"	NPSH	2-3/4"	S26275
2½"	NPSH	2-13/16"	S26281
2½"	NPSH	2-7/8"	S26287
1½"	NH (NST)	1-11/16"	S16168F
1½"	NH (NST)	1-3/4"	S16175F
1½"	NH (NST)	1-13/16"	S16181F
2½"	NH (NST)	2-11/16"	S26268F
2½"	NH (NST)	2-3/4"	S26275F
2½"	NH (NST)	2-13/16"	S26281F
2½"	NH (NST)	2-7/8"	S26287F

- *Double jacket*
- Lugs on female and males
- Working pressure: **360 PSI**

Hose Size	Thread Type	Bowl Size	Dixon Part #
1½"	NPSH	1-7/8"	D16187
1½"	NPSH	1-15/16"	D16193
1½"	NPSH	2-1/16"	D16206
2½"	NPSH	3"	D263
1½"	NH (NST)	1-7/8"	D16187F
1½"	NH (NST)	1-15/16"	D16193F
1½"	NH (NST)	2-1/16"	D16206F
2½"	NH (NST)	3"	D263F

- Other sizes and threads are also available. *Consult the factory for pricing and availability.*
- For females or males only, *consult the factory for pricing and availability.*

* **Under no circumstance should the fittings be used beyond the working pressure of the hose.**

Assembled hose should be hydrostatically proof tested before use, and thereafter in accordance with NFPA 1962.